TestingWhiz

Code Less, Test More

Code Less, Test More.

USER MANUAL

Contents

1. GENERAL INFORMATION 20
1.1. Target Audience 20
1.2. System Requirements 20
1.3. Platform Support 20
1.4. Browser Support 21
1.5. Mobile Support 21
1.5.1. Android Device Support 22
1.5.2. iOS Device Support 22
2. UNDERSTANDING TESTINGWHIZ 23
2.1. Welcome Screen 25
2.2. Menu Bar 26
2.2.1. File 26
2.2.2. Edit 28
2.2.3. Settings 29
2.2.4. Tools 62
2.2.5. Support 66
2.2.6. Help 68
2.3. Tool Bar 70
2.4. Menu Tabs 73
2.4.1. Test Project 73
2.4.2. Data Table 74

2.4.3. Objects 74
2.5. Test Editor Tabs 75
2.5.1. Test Editor 75
2.5.2. Test Data 76
2.5.3. Outline 78
2.5.4. Project Details 78
2.5.5. Reports 79
2.6. Test Command, Methods and Variable Tab 80
2.6.1. Test Command 80
2.6.2. Methods 81
2.6.3. Variable 82
2.7. Quick Access Icons 83
2.7.1. Show View 83
2.7.2. Record 84
2.7.3. Console 84
3. LEARNING TO CREATE & MANAGE TEST PROJECTS, TEST CASES & TEST SCRIPTS 85
3.1. Learn from a Sample Test Case 85
3.2. Process to Create & Manage Test Project, Test Suite & Test Scripts 88
3.2.1. Steps to Create New Project 88
3.2.2. Steps to Add & Manage Test Suite under Test Project 90
3.2.3. Steps to Add & Manage Test Cases & Test Scripts 96
4. PROCESS OF CREATING, EXECUTING, REPORTING & MANAGING TESTS IN TESTINGWHIZ 110

4.1. Create, Record and Import Automation Test Scripts 110
4.1.1. Create Test Automation Scripts Manually 110
4.1.2. Record to Create Test Script Using Internal Browser 110
4.1.3. Record to Create Test Script Using External Browser 118
4.1.4. Import Test Script 124
4.2. Execute Test Script 128
4.2.1. Select Browser 128
4.2.2. Run Test Script 129
4.3. Pause Test Execution 130
4.4. Stop Test Execution 131
4.5. Move to Next Step 132
4.6. Check Progress and Execution Log 133
4.6.1. Clear or Export Logs 133
4.7. Test Report 134
4.7.1. Analyze Report 135
4.8. Log a Defect 137
4.9. Email Report 139
5. KEYWORD-DRIVEN & DATA DRIVEN TESTING IN TESTINGWHIZ 140
5.1. Keyword-driven Testing 140
5.1.1. Setting up Keyword-driven Test Script 140
5.2. Data Driven Testing 141
5.2.1. Setting up Data-driven Test Script 141

6. IMPORTANT FUNCTIONS OF TESTINGWHIZ 145
6.1. Data Flow Diagram View/Outline view 145
6.2. Object Eye 146
6.3. Object Repository 146
6.4. Methods 148
6.4.1. Process of Creating and Calling Method 148
6.5. Image Comparison 156
6.5.1. How Image Comparison Works 156
6.6. Fork 161
6.6.1. Test Case Forking 161
6.6.2. Test Step Forking 165
6.7. Mobile Test Execution 169
6.7.1. Android Environment Setup for Mobile Test Execution 171
6.7.2. iPhone Environment Setup for Mobile Test Execution 176
6.8. Data Cleansing via Data Validation 181
6.8.1. How to Perform Data Cleansing 181
6.9. Risk Based Testing 184
6.9.1. How to perform Risk Based Testing (RBT) 184
6.10. Web Services Testing 187
6.10.1. RESTful Web Services Testing 187
6.10.2. SOAP Web Services Testing 190
6.11. Execution via TestingWhiz CI Plugin 193

6.12. Accessing DataTable Values Without Loop 196
6.13. Importing Data from Other Test Projects 196
7. TEST COMMANDS IN TESTINGWHIZ 202
7.1. How to Add a Test Command 202
7.1.1. Drop-down List 202
7.1.2. Drag & Drop Test Command 204
7.1.3. Double Click Test Command 206
7.2. How to Add an Action Corresponding to a Particular Test Command 206
7.2.1. Drop-down List 206
7.2.2. Drag & Drop Action 207
7.2.3. Double Click Action 208
8. LIST OF TEST COMMANDS & CORRESPONDING ACTIONS 209
8.1. Break 209
8.2. Call Method 210
8.3. Capture 211
8.3.1. Webscreen 211
8.3.2. Snapshot 212
8.4. Check 213
8.4.1. Text 214
8.4.2. Title 214
8.4.3. Checked 214
8.4.4. Unchecked 214

8.4.5. Visible 214
8.4.6. Invisible 215
8.4.7. Enabled 215
8.4.8. Disabled 215
8.4.9. Exists 215
8.4.10. Selected:value 215
8.4.11. Selected:index 215
8.4.12. Text:value 216
8.4.13. Cookie 216
8.4.14. Single Occurrence 216
8.4.15. Text Ignore Case 216
8.4.16. URL Reachable 217
8.4.17. Image 217
8.5. Click 218
8.6. Clean 219
8.7. Click and Wait 220
8.8. Compare 221
8.8.1. Less than 222
8.8.2. Less than or equal to 222
8.8.3. Greater than 222
8.8.4. Greater than or equal to 222
8.8.5. Equal to 222

8.8.6. Not equal to 222
8.8.7. Data Table 222
8.8.8. Between Range 223
8.9. Continue 224
8.10. DataTable 225
8.10.1. Size 225
8.10.2. Row 225
8.11. Database 226
8.11.1. Fetch 227
8.11.2. Query 229
8.11.3. Comparison 230
8.12. Delete 232
8.12.1. All Cookies 232
8.12.2. Cookie 232
8.13. Dynamic Input 233
8.14. Else 234
8.15. ElseIf 235
8.15.1. Text 236
8.15.2. Title 236
8.15.3. Checked 236
8.15.4. Unchecked 236
8.15.5. Visible 236

8.15.6. Invisible 236
8.15.7. Enabled 236
8.15.8. Disabled 237
8.15.9. Selected:index 237
8.15.10. Selected:value 237
8.15.11. Text:value 237
8.15.12. Exists 237
8.15.13. Compare 237
8.15.14. Compare Ignore Case 237
8.15.15. isBlankOrNull 238
8.15.16. Contains 238
8.15.17. URL Reachable 238
8.15.18. Image 238
8.15.19. Less than 238
8.15.20. Less than or equal to 238
8.15.21. Greater than 238
8.15.22. Greater than or equal to 238
8.15.23. Equal to 239
8.15.24. Not equal to 239
8.15.25. Between Range 239
8.16. ElseIf-Not 240
8.16.1. Text 240

8.16.2. Title 241
8.16.3. Checked 241
8.16.4. Unchecked 241
8.16.5. Visible 241
8.16.6. Invisible 241
8.16.7. Enabled 241
8.16.8. Disabled 241
8.16.9. Selected:index 241
8.16.10. Selected:value 241
8.16.11. Text:value 242
8.16.12. Exists 242
8.16.13. Compare 242
8.16.14. Compare Ignore Case 242
8.16.15. IsBlankOrNull 242
8.16.16. Contains 242
8.16.17. URL Reachable 243
8.16.18. Image 243
8.16.19. Less than 243
8.16.20. Less than or equal to 243
8.16.21. Greater than 243
8.16.22. Greater than or equal to 243
8.16.23. Equal to 243

8.16.24. Not equal to 243
8.16.25. Between Range 244
8.17. End If 244
8.18. Enter Authentication 245
8.19. Execute 245
8.19.1. JavaScript 245
8.19.2. RESTful Web Service 245
8.19.3. SOAP Web Service 246
8.20. Exit 247
8.20.1. Test Case 247
8.20.2. Test Project 247
8.20.3. Test Suite 248
8.21. Export To 248
8.21.1. XML 249
8.21.2. CSV 249
8.22. FTP 250
8.22.1. Upload 250
8.22.2. Is Exist 251
8.22.3. Download 251
8.22.4. Delete 251
8.23. Fail 251
8.24. Fork End 252

8.25. Fork Start 253
8.26. Get 254
8.26.1. Text 254
8.26.2. Value 255
8.26.3. Table Row Count 255
8.26.4. Table Column Count 255
8.26.5. Attribute 255
8.26.6. Table Cell Data 255
8.26.7. Title 255
8.26.8. Current Page URL 255
8.26.9. Alert Text 255
8.26.10. Page Source 256
8.26.11. Table 256
8.26.12. Elements 256
8.27. Highlight 256
8.28. If 257
8.28.1. Text 257
8.28.2. Title 257
8.28.3. Checked 257
8.28.4. Unchecked 257
8.28.5. Visible 258
8.28.6. Invisible 258

8.28.7. Enabled 258
8.28.8. Disabled 258
8.28.9. Selected:index 258
8.28.10. Selected:value 258
8.28.11. Text:value 258
8.28.12. Exists 259
8.28.13. Compare 259
8.28.14. Compare Ignore Case 259
8.28.15. IsBlankOrNull 259
8.28.16. Contains 259
8.28.17. URL Reachable 259
8.28.18. Image 259
8.28.19. Less than 260
8.28.20. Less than or equal to 260
8.28.21. Greater than 260
8.28.22. Greater than or equal to 260
8.28.23. Equal to 260
8.28.24. Not equal to 260
8.28.25. Between Range 260
8.29. If-Not 261
8.29.1. Text 261
8.29.2. Title 261

8.29.3. Checked 262
8.29.4. Unchecked 262
8.29.5. Visible 262
8.29.6. Invisible 262
8.29.7. Enabled 262
8.29.8. Disabled 262
8.29.9. Selected:index 262
8.29.10. Selected:value 262
8.29.11. Text:value 263
8.29.12. Exists 263
8.29.13. Compare 263
8.29.14. Compare Ignore Case 263
8.29.15. IsBlankOrNull 263
8.29.16. Contains 263
8.29.17. URL Reachable 263
8.29.18. Image 264
8.29.19. Less than 264
8.29.20. Less than or equal to 264
8.29.21. Greater than 264
8.29.22. Greater than or equal to 264
8.29.23. Equal to 264
8.29.24. Not equal to 264

8.30. Input 265
8.31. IsSorted 266
8.31.1. Ascending 266
8.31.2. Descending 267
8.32. KeyPress 267
8.32.1. Enter 267
8.32.2. Escape 268
8.32.3. Tab 268
8.32.4. Refresh 268
8.32.5. F1 268
8.32.6. F3 268
8.32.7. F6 268
8.32.8. F10 268
8.32.9. F11 268
8.32.10. Page Up 269
8.32.11. Page Down 269
8.32.12. Up 269
8.32.13. Down 269
8.32.14. Left 269
8.32.15. Right 269
8.33. Loop End 270
8.34. Loop Start 271

8.35. Math 271
8.35.1. Absolute Value 272
8.35.2. Integer Value 272
8.35.3. Floor Value 272
8.35.4. Ceiling Value 272
8.35.5. Add 273
8.35.6. Subtract 273
8.35.7. Random Number 273
8.36. Move 273
8.36.1. To Next Page 274
8.36.2. To Previous Page 274
8.36.3. To Window 274
8.36.4. To Frame 275
8.36.5. To Parent 275
8.37. Open Page 275
8.38. Parse 276
8.38.1. JSON Message 276
8.38.2. XML Message 277
8.39. Perform 279
8.39.1. Right Click 279
8.39.2. Mouse Over 279
8.39.3. Scroll Up 279

8.39.4. Scroll Down 280
8.39.5. Close 280
8.39.6. Set:variable 280
8.39.7. Accept Alert 280
8.39.8. Reject Alert 280
8.39.9. Set:globalvariable 280
8.39.10. Double Click 280
8.39.11. Drag and Drop 280
8.40. Run Command 281
8.41. Run Remote Command 282
8.42. Search 283
8.42.1. Object 283
8.43. Select 284
8.43.1. Value 284
8.43.2. Index 284
8.44. Send Mail 285
8.45. Server 286
8.45.1. GET Request 286
8.45.2. POST Request 287
8.45.3. Checkpoint 287
8.45.4. Callback 287
8.46. Set 287

8.46.1. Value 287
8.47. String 288
8.47.1. Extract Substring 288
8.47.2. To Lower 289
8.47.3. To Upper 289
8.47.4. Trim 289
8.47.5. Length 289
8.47.6. Compare 289
8.47.7. Compare Ignore Case 289
8.47.8. Concatenate 289
8.47.9. IsBlankOrNull 289
8.47.10. ToNumber 290
8.47.11. Contains 290
8.47.12. Split 290
8.47.13. Remove 290
8.48. Trigger 291
8.48.1. Value 291
8.49. Verify 292
8.49.1. Text 292
8.49.2. Title 292
8.49.3. Checked 293
8.49.4. Unchecked 293

8.49.5. Visible 293
8.49.6. Invisible 293
8.49.7. Enabled 293
8.49.8. Disabled 293
8.49.9. elected:index 293
8.49.10. Selected:value 293
8.49.11. Text:value 294
8.49.12. Exists 294
8.49.13. URL Reachable 294
8.49.14. Image 294
8.49.15. Test Ignore Case 294
8.49.16. Cookie 295
8.49.17. Single Occurance 295
8.50. Wait 295
8.50.1. For Element 295
8.50.2. For Time 296
8.51. While End 296
8.52. While Start 297
8.53. Write Message To Report 298

1. GENERAL INFORMATION

1.1. Target Audience

This manual is intended to help QA engineers and software testers automate the testing of web and cloud-based applications using TestingWhiz. It can also be used by Business Analysts, Project Managers, Test Leads and other Stakeholders who are involved in testing activities for analysis and estimation purposes.

1.2. System Requirements

Operating System: Windows XP/ Windows Vista/ Windows 7/ Windows 8

Processor: Intel Pentium 4 or later

RAM: 1 GB (2 GB Recommended)

Free Disk Space: 400 MB

Java Version: JRE 6 or later

1.3. Platform Support

TestingWhiz can be used to create Automation Test Scripts only on Windows. However, the test scripts created using TestingWhiz can be executed on different operating systems like Mac and Linux. For information on how TestingWhiz Automation Tests can be run on MAC or Linux, please contact us.

1.4. Browser Support

TestingWhiz supports

- Internet Explorer: Version 9, 10 and 11
- Mozilla Firefox: Version 3.6 to version 39
- Google Chrome: Version 36 to version 43
- Apple Safari: Version 5.x
- Opera: Version 11 & 12.x

User can use any of the above browsers as a default browser to execute the Automation Test Scripts created using TestingWhiz.

Refer section - **Configuration** to learn how to set the default browser.

[**Note:** *TestingWhiz also supports HTML5 partially.*]

1.5. Mobile Support

TestingWhiz also comes with a Mobile support to perform mobile and web testing on Android and iOS devices. Mobile test execution can be done by connecting the real device with the system or via Simulator.

1.5.1. Android Device Support

TestingWhiz provides mobile web test execution on Android Mobile Phones & Tablets. Currently it supports the following Android versions:

- Gingerbread (2.3)
- Honeycomb (3.0)
- Ice Cream Sandwich (4.0)
- Jelly Bean (4.3)
- KitKat (4.4)
- Lollipop (5.0)

1.5.2. iOS Device Support

TestingWhiz provides mobile web test execution on iOS devices like iPhones and iPads. Currently it supports the following iOS versions

- IOS 7.1 or 8.1

2. UNDERSTANDING TESTINGWHIZ

TestingWhiz has a straightforward user interface for quick, effective and trouble-free testing.




TestingWhiz Enterprise - New File
File Edit Settings Tools Support Help
Menu Bar
New Open Import Export Record Execute Next Pause Stop
Log a Defect
Email Report
Image Comparison
Database Comparison
Test Management Tool
Tool Bar
Test Project Data Table Object
Menu Tabs
Test Project
Test Commands, Methods & Variable Tabs
Test Command Methods Variable
Search
Break
Call Method
Capture
Check
Click
Click And Wait
Compare
Continue
Data Table
Database
Test Editor Test Data Outline Project Details
Test Editor Tabs
Project Information
Project Name *
Test Project
Product URL
Test Execution Cycle
Environment
Development
Project Description
Build Version
Build Date
5/ 4/2015
Base URL
Automation Prepared By
Save
Reset

2.1. Welcome Screen

When a user launches TestingWhiz tool, a Welcome Screen appears highlighting four functions with a brief explanation of each function. User can simply click on the function name (Recording, Configuration, Check Samples or Help) to perform it.

- **Recording**: To record test case execution steps
- **Configuration**: To set configuration preferences (Set up default browser, language, etc.)
- **Check Samples**: To open a list of sample scripts
- **Help**: To get help for using TestingWhiz



2.2. Menu Bar

Menu Bar contains important functions of TestingWhiz in a drop-down format. It provides instant access to different tasks and actions along with short-cuts for seamless test project execution.



2.2.1. File

Open File menu to perform the following functions:



2.2.1.1. New

Click New to create a New Test Project.

2.2.1.2. Open

Click Open to open an existing Project/Script (.twiz file).

2.2.1.3. Open Sample

Click Open Sample to view a list of sample script.

2.2.1.4. Save

Click Save to save the Test Project.

2.2.1.5. Save As

Click Save As to save the existing file with a new name and at the new location.

2.2.1.6. Import Test Project

Click Import Test Project to import Test Suite/Cases/Datatable/Methods to existing test project.

2.2.1.7. Import from Excel

Click Import from Excel to import existing scripts from Excel file to TestingWhiz.

2.2.1.8. Export to Excel

Click Export to Excel to save and export existing test scripts from TestingWhiz to Excel file.

2.2.1.9. Share twiz Project

Click Share twiz Project to email existing .twiz Project/Script.

2.2.1.10. License Information

Click License Information to view details of the license – type, start date, end date, edition, etc.

2.2.1.11. Exit

Click Exit to exit TestingWhiz application.

2.2.2. Edit

Use of Edit menu provides the following options:

2.2.2.1. Undo

Click Undo to undo/reverse the last step(s).



2.2.2.2. Redo

Click Redo to redo/repeat the last step(s).

2.2.3. Settings

Use settings to set preferences and defaults in TestingWhiz



2.2.3.1. Configuration

Click Configurations to set up General preferences, Execution, Mobile Web Testing, Screen, Mail, Recording Rules, Database configuration, TestingWhiz Grid, Bug Tracking Tool and Test Management Tool etc.

I. General: Set up general preferences.



Application Language	Select default language to write application test cases – English, Français, Duetsch, Nederlands, Español, & Italiano. [**Note:** *Changes in language will be effective after Restart.*]
Report Language	Select default language to generate test report – English, Français, Duetsch, Nederlands, Español, & Italiano. [**Note:** *Changes in language will be effective after Restart.*]
Select Color to Highlight Image Difference	Select default color to highlight image difference – Red, Green & Yellow. [**Note:** *Image difference color will be highlight in "Image Comparison Report" after completion of test execution.*]
Resolution For Image Comparison	Select resolution of Image Comparison– Low or High. [**Note:** *Resolution for Image Comparison will be highlight in "Image Comparison Report" after completion of test execution.*]
Enable sound effects	Tick this option to enable or disable sound effect.
Share work space data among users	Tick this option to share work space data among other users.
Restore Defaults	Click Restore Defaults to reverse to default settings.
Apply	Click Apply to confirm and save the settings.

II. Execution: Set up execution preferences.



Browser	Select default browser from the available browsers – Internet Explorer, Mozilla Firefox, Google Chrome, Safari Opera and Android.
Delay Value	Set up speed to execute/play the test script. [**Note:** *Value will be displayed in Milliseconds.*]
Trend Analysis Value	Set up the maximum bars in Trend Analysis column. [**Note:** *By default value 10 appear.*]
Turn Off Object Eye	Tick this option to turn off Object Eye feature for manually added steps.
Pause Test Execution	Tick this option to pause the test execution. [**Note:** *Allows user to select correct object at the time of test execution, also helps to handle dynamic object.*]
Fall back on another browser	Tick this option to switch to another browser if default browser is not compatible. [**Note:** *View details in execution logs in executed report.*]
Export Project details in Bug Tracking Tool	Tick this option to export project details into the bug tracking tool while opening a new bug ticket.
Restore Defaults	Click Restore Defaults to reverse to default settings.
Apply	Click Apply to confirm and save the settings.

III. Mobile Web testing: Set up Android or iOS test execution server preferences.

Select Platform	Select the platform between Android and iOS for mobile web testing.



A. Mobile Web Testing for Android



URL	Enter the Server URL – URL of an Appium server which is connected to Android device.
Device Name	Enter the device name in case of simulation testing.
Browser	Select a browser from the drop-down.
Test Connection	Click Test Connection to test the connection with the Appium Server.
Restore Defaults	Click Restore Defaults to default settings.
Apply	Click Apply to configure and save the settings.

B. Mobile Web Testing for iOS



URL	Enter the URL of an Appium Server which is connected to iOS device.
Device Name	Enter the device name in case of simulation testing.
Platform Version	Enter the platform version of the iOS device.
Browser	Select a browser from the drop-down.
Test Connection	Click Test Connection to test the connection with the Appium Server.
Restore Defaults	Click Restore Defaults to default settings.
Apply	Click Apply to configure and save the settings.

IV. Report: Set Up Execution Report Preferences.



Chart Style	Select execution report chart style available from drop down: Pie/Icicle.
Always Capture Failure Screenshot	Tick this option to capture screenshots of the failed test cases.
Use Custom Report Path	Tick this option to store reports at any other custom path of your choice rather than the default location.
Restore Defaults	Click Restore Defaults to reverse to default settings.
Apply	Click Apply to confirm and save the settings.

V. Recording: Set up recording rules to be performed while recording test scripts using internal as well as external browsers.



Add	Click Add to insert more recording rules to suit the recording behavior before generating scripts with Record and Playback feature.
Remove	Click Remove to delete a particular or a set of recording rules from the existing rules to suit the recording behavior requirement.
Default	Click Default to get the default list of events (recording rules).

For more details about Recording using Internal Browser, kindly refer section – **Record to Create Test Script Using Internal Browser**

For more details about Recording using External Browser, kindly refer section - **Record to Create Test Script Using External Browser**

[**Note:** *By default, TestingWhiz provides 18 Events (recording rules)*.]

VI. Data Validation Rules: Set up data validation rules for the process of data cleansing.



[**Note:** *By default, TestingWhiz provides 9 Alias for data validation*.]

Add	Click Add to insert more Alias, Java Expression and Input for data validation.
Edit	Click Edit to edit Alias, Java Expression and Input for data validation.
Remove	Click Remove to remove a particular or a set of Alias and related Java Expression and Input to suit the requirement for data validation.

VII. Screen: Set up display preferences.



Show Welcome Screen	Tick this option to view Welcome Screen on every start-up of the application.
Show Active Screen	Tick this option to view Active Screen or current screen during test execution.
Restore Defaults	Click Restore Defaults to reverse to default settings.
Apply	Click Apply to confirm and save the settings.

VIII. Mail: Configure mail account with TestingWhiz to send test reports through mail.

SMTP Server	Enter SMTP Server (Outgoing Mail Server) details of the User's Email Address.



SMTP Port	Enter SMTP Port details to authorize User's Email Address.
User Name & Password	Enter Users Server credential - Username & Password to configure Email Address in TestingWhiz.
To	Enter Recipient's Email Address.
Subject	Enter Subject of the Email.
Message Content	Enter Message Content (Optional).
Signature	Enter Signature (Optional).
Send Test Mail	Click Send Test Mail to test whether the Email has been configured correctly or not (Optional).
Apply	Click Apply to confirm and save the settings.

IX. Database: To fetch data directly into the Data table and run raw queries.



Database Type	Click Add and select database type from the drop-down – MySQL, MSSQL, ORACLE, DB2, PostgreSQL, AWS Teradata or HortonWorks Hadoop.
Database Alias	Enter the Database Alias.
Database Name	Enter the Database Name.
Host	Enter the location (IP address) where the database is to be hosted.
Port	Enter the Port of the Database.
Username & Password	Enter the Username & Password to authorize the Database.
Edit	Click Edit to edit items in the Database.
Remove	Click Remove to remove particular items from the Database.
Import	Click Import to integrate Database Connection configuration in TestingWhiz.
Export	Click Export to save the Database configuration so that you don't have to repeat the connection setting procedure again.
Test Connection	Click Test Connection to test the connection with the Database.
Apply	Click Apply to configure and save the settings.

X. FTP: To upload files to server.



Connect With	Click Add and select FTP type from the drop-down – FTP or SFTP.
Alias	Enter the FTP Alias.
Host Name	Enter the location where the FTP is to be hosted.
Port	Enter the Port of the FTP.
Username & Password	Enter the Username & Password to authorize the FTP.
Edit	Click Edit to edit items in the FTP.
Remove	Click Remove to remove particular items from the FTP.
Test Connection	Click Test Connection to test the connection with the FTP.
Apply	Click Apply to configure and save the settings.

XI. TestingWhiz Grid: To distribute the test execution across multiple machines and reduce the execution time.



Hub Server URL	Enter Hub Server URL – URL of a centralized server/main machine which is connected with other machines.
Test Connection	Click Test Connection to test the connection with the Hub Server URL.
Restore Defaults	Click Restore Defaults to default settings.
Apply	Click Apply to configure and save the settings.

XII. Bug Tracking Tool: To configure Bug Tracking Tool Accounts to post bugs directly from TestingWhiz.



Select Bug Tracking Tool	Select the Bug Tracking Tool – Jira, Mantis or FogBugz.
Alias	Click Add and enter Alias of the Bug Tracking Tool.
URL	Enter URL of the Bug Tracking Tool.
Username & Password	Enter Username & Password to establish connection with the Bug Tracking Tool.
Test Connection	Click Test Connection to test reporting with the selected Bug Tracking Tool.
Apply	Click Apply to configure and save the settings.

XIII. Test Management Tool: To configure Test Management Tool (Quality Center) with TestingWhiz.



Alias	Click Add and enter the Alias name of the Test Management Tool.
Quality Centre URL	Enter URL of the Quality Center.
Username & Password	Enter Username & Password to authorize the Test Management Tool.
Test Connection	Click Test Connection to test the connection with the Test Management Tool.
Apply	Click Apply to configure and save the settings.

XIV. Risk Based Testing: Configure settings for executing Risk Based Testing.



RBT enabled execution	Tick this option to enable Risk Based Testing.
Prioritize Test Cases	Select options among High, Medium and Low to prioritize Test Case execution with Risk Based Testing.

XV. Install/Update: Configure settings related to Installation & Updates of TestingWhiz.



Browsing for Updates	Select option to show only latest versions of the available software OR show all versions of the available software while browsing for updates.
Software Compatibility for an Install Wizard	Select option to either: Open Wizard to review/change selections OR Report only problems OR Ask me what to do when the software is not compatible for the install wizard.

A. AutoTest: Available Software Sites



Add	Enter Name of the available software and location of the file from Local or Archive folder
Edit	Click Edit to change the name and location of the already added software site
Remove	Click Remove to remove existing software site
Reload	Click Reload to reload the software site in TestingWhiz
Enable/Disable	Click Enable/Disable buttons to check or uncheck existing software site
Import	Click Import to integrate software sites in TestingWhiz
Export	Click Export to save the list of software sites



B. Install/Update: Automatic Updates



Find New Updates	Tick this option to automatically search for new updates
Update Schedule	Select option to either look for updates each time TestingWhiz is started OR specify the day and time to look for updates
Download Options	Select option to either search and notify for new updates OR download updates automatically
When updates are found	Select option to either notify when updates are found OR set timings to remind for updates automatically
Restore Defaults	Click Restore Defaults to reverse to default settings
Apply	Click Apply to configure and save settings

2.2.3.2. Reset Perspective

Click Reset Perspective to restore the default settings.



2.2.4. Tools

Use Tools to perform the following functions:



2.2.4.1. Scheduler

I. Manage Jobs

Click Scheduler >> Manage Jobs to schedule and manage jobs in TestingWhiz.





Add: Click Add to Schedule a Job(s) and enter the details.

Job Name	Enter the Name of the job to be scheduled.
Project	Enter the path/location of the Test Script(s) to be scheduled.
RBT enabled execution	Tick this option to perform Risk-based Testing of the selected Test Script.

Trigger	Select the time to Trigger a job schedule. [**Note:** *User can customize Trigger Time based on Minute, Hour, Day, Week and Month.*] 
Browser	Select the Browser to run the Test Script(s)
Send Report To	Enter the email addresses to Send Report to individuals. [**Note:** *This function will work only after a user has set Mail Preferences.*]

Edit: Click Edit to edit the details of the scheduled job(s).

Remove: Click Remove to remove specific job(s) from the list.

Duplicate: Click Duplicate to copy a scheduled job.

Save: Click Save to save the details of the scheduled job.

Trend Analysis: It facilitates to view the Trend of scheduled jobs.

II. Job History

Click Job History to view a history of the scheduled + executed jobs.

Select from the drop-down: All, Today, Last 7 days, Last 15 days, Last 30 days, Last 90 days. Similarly, a user can clear history of the scheduled + executed jobs by selecting the period from the drop-down list.



2.2.4.2. Server Start

Click Server Start to execute on Jenkins.

[**Note:** *To avail Jenkins integration functionality on your TestingWhiz, email at sales@testing-whiz.com.*]

2.2.5. Support

Click Support Tab to get personalized support from TestingWhiz Support Team related to the tool usage and queries.



2.2.5.1. Whiz Support

Click Whiz Support to directly email issues, queries and concerns related to TestingWhiz to the Support Team. Enter the Subject and Message Content. Once finished, click to send the e-mail.



[**Note:** *Mailings through Whiz Support will work only after the Mail server connection has been established.*]

2.2.5.2. Support Desk

Clicking on Support Desk will redirect a user to TestingWhiz Support Web Page. From this web page, a user can get answers from the community forums, submit requests to the Support Desk and check updates & announcements.


https://testingwhiz.zendesk.com/home
TestingWhiz
TestingWhiz: Codeless Automation
login | sign up
HOME
FORUMS
SUBMIT A REQUEST
CHECK YOUR EXISTING REQUESTS
Welcome to TestingWhiz: Codeless Automation Customer Service!
Stay updated with announcements, get answers from the community, and share your feature suggestions with us.
You can also submit a request or send us an email at support@testingwhiz.zendesk.com.
Forums
Search
Overview | Recent
Announcements (0) »
No topics found
Tips & Tricks (0) »
No topics found - Add Article »
Feature Requests (0) »
No topics found - Add Article »
TestingWhiz Forum - Automated Web Tes... (0) »
No topics found - Add Article »

2.2.6. Help

Use Help to access following functions:

2.2.6.1. Welcome

Click Welcome to go to TestingWhiz Welcome Page.

2.2.6.2. User Guide

Click User Guide to open and view the TestingWhiz User Manual in PDF Format.

2.2.6.3. About TestingWhiz

Click on About TestingWhiz to avail information related to TestingWhiz application version, build date, etc.



2.3. Tool Bar



Features	Description
	To create a New Test Project in TestingWhiz.
	To open an Existing Project.
	To import the Script(s) from the Excel file to TestingWhiz. [**Note:** *Available only after user has created script(s) in Excel.*]
	To export recorded or automated Test Script(s) to Excel.

	To start recording Test Case(s). [**Note:** *The color will change to Red*  *, which indicates that the recording is in progress.]* Click  to start recording test case(s) in external browser (Google Chrome). Click  to stop recording of Test Case(s).
	To execute a Test Case. Click down arrow to select the browser or platform for execution. [**Note:** *If there is no Test Script present in the Test Project, this button will remain disabled.*]
	To go to the Next Step during Test Execution. [**Note:** *This button will be enabled only if a test script execution is paused / is at Toggle BreakPoint.*]
	To Pause the Test Execution process. [**Note:** *This button will be active only when a test is being executed.*]
	To Stop the Test Execution process. [**Note:** *This button will be active only when a test is being executed.*]
	To log issues (if any) in the Bug Tracking Tool during test execution. [**Note:** *A window to select the Bug Tracking Tool will appear.*] [**Note:** *This feature will function only if a user has set Bug Tracking Tool credentials in the Configuration section.*]

Email Report	To mail Test Report(s). [**Note:** *A window to enter the Email Address(es), Subject and the Message Content will appear.*] [**Note:** *This feature will function only if a user has set Email preferences in the Configuration section.*]
Image Comparison	To view Image Comparison report. [**Note:** *This feature will be enabled only after completion of Image Comparison.*]
Database Comparison	To view Database Comparison report. [**Note:** *This feature will be enabled only after completion of Database Comparison.*]
Test Management Tool	To integrate Test Projects, Defects, etc. with the Test Management Tool. [**Note:** *A window to enter the Email Address(es), Subject and the Message Content will appear.*] [**Note:** *This feature will function only if you have set Test Management Tool preferences in the Configuration section.*]

2.4. Menu Tabs

2.4.1. Test Project

Use Test Project tab to create, delete and move Test Suite(s) and Test Case(s).



Function	Description
	To add new Test Suite(s) and Test Case(s).
	To delete existing Test Suite(s) or Test Case(s).
	To move up a particular Test Suite(s) or Test Case(s).
	To move down a particular Test Suite(s) or Test Case(s).
	To highlight a particular Test Suite or Test Case.

User can manually create or modify the Test Case(s) and create Test Step(s) using the Test Case Editor. For more details, refer Section – **Steps to Create & Run Test Case**.

2.4.2. Data Table

Use Data Table to add/import multiple data sets and input values for executing Test Case(s).



Function	Description
	To add new Data Table for inserting Test Data.
	To delete a particular Data Table containing Test Data.

2.4.3. Objects



Objects displays the repository of Test Objects.

Features	Description
	To clean up existing Test Objects.
	To view Test Objects by URL or Tags [**Note:** *User can change the View of Test Objects from View by URL to View by Tag using the Dropdown as shown here*  .]

To learn more, kindly refer Section – **Object Repository**

2.5. Test Editor Tabs

2.5.1. Test Editor

Use Test Editor to add and manage Test Steps.



Function	Description
	To cut particular Test Step(s) created under a specific Test Case.
	To copy particular Test Step(s) created under a specific Test Case.
	To paste already cut/copied Test Step(s).
	To add new Test Step(s) within a particular Test Case.
	To delete existing Test Step(s) within a particular Test Case.
	To move up a particular Test Step.
	To move down a particular Test Step.

2.5.2. Test Data

Use Test Data to render values of Data Table.





Import from Excel: Click to import data from Excel file to Data Table.

Precondition: Data Table in which user has to import data.

After selecting file "Excel Statistic" window to be opened which will provide below selection to user.

a) User can select any one Worksheet from Worksheet list of Excel File.

b) User can select all columns or multiple columns or single columns from the Column List of Selected worksheet from List.

c) User can input the no. of rows which he wants from Excel file.

d) User also get the total no of columns and no of rows of selected worksheet on "Excel Statistic" window.

e) After click on "Import Data" button as per the user selection all records are imported into selected placeholder.

Function	Description
	To cut particular Data table Value/Test Step.
	To copy particular Data table Value/Test Step.
	To paste already cut/copied Data table Value/Test Step.
	To add new Data table Value/Test Step.
	To delete a particular Data table Value/Test Step.
	To move up a particular Data table Value/Test Step.
	To move down a particular Data table Value/Test Step.

2.5.3. Outline

Use Outline to view the Test Case in Data Flow Diagram.



To learn more, kindly refer section – **Outline View/Visual Presentation View**.

2.5.4. Project Details

Use Project Details Tab to view all the details – Project Name, Product URL, Environment and Product Description – related to the Test Project created.



[Note: *Project Details Tab will be displayed only when a user clicks on the Test Project Folder as shown above.*]

2.5.5. Reports

Use Reports tab to view the reports; i.e., percentage of passed or failed Test Case(s).



Use Backward and Forward buttons to view alternate Reports.

[**Note:** *Reports Tab will be enabled only after a Test Case has been executed; if not, this function will not be visible in the Test Editor Tab.*]

2.6. Test Command, Methods and Variable Tab

2.6.1. Test Command

Use Test Command Tab to view the list of available commands defined in the system.



Function	Description
	To expand all the functions of a selected commands.
	To collapse all the expanded functions of a selected commands.

For more details on Test Command, kindly refer chapter **Test Commands & Corresponding Actions in TESTINGWHIZ**.

2.6.2. Methods

Use Methods Tab to add and apply methods of choice in the test execution process:



Function	Description
+	To create new Method.
−	To delete a particular Method.

For more details on Methods, kindly refer Section - **Methods**.

2.6.3. Variable

Use Variable Tab to view the value of variables used to Perform Command with type - Local & Global Variable.



Refer Section – **Perform** Command in Test Command Section to view more.

2.7. Quick Access Icons

Use the Quick Access Icons on the left side to get instant access to Menu items, Recording function and Console.

2.7.1. Show View

Click to view the quick menu as shown below:



Click on **Other** to directly view functions of Menu as shown below:



2.7.2. Record

Click to start recording the Test Script.

2.7.3. Console

Click to view Console.

3. LEARNING TO CREATE & MANAGE TEST PROJECTS, TEST CASES & TEST SCRIPTS

TestingWhiz works on the principle of codeless testing. It allows users to build test scripts without presupposing programming or technical knowledge. The naming conventions of Test Commands and Actions are provided in a simple and functional language to help a user create and understand Automation Test Scripts easily.

3.1. Learn from a Sample Test Case

TestingWhiz includes several sample test cases to help a user get acquainted with the process.

From Welcome Screen, user can **Open Sample** Test Cases by clicking on **Check Samples**.



List of the Sample scripts opens on screen as shown below in the screenshot.



OR

To view a Sample Case, click on the **Open Sample** in **File** menu and select the type of the Test Case.



3.2. Process to Create & Manage Test Project, Test Suite & Test Scripts

3.2.1. Steps to Create New Project

3.2.1.1. Add a New Project

Click

from the Tool Bar.



OR

Click on **File** and then click **New**.



Enter the Project Information in the form as shown below and click **Save**.



3.2.2. Steps to Add & Manage Test Suite under Test Project

3.2.2.1. Add a New Test Suite

Select the Test Project as created in Step **3.2.1.1** and click button to add a **New Test Suite** within the Test Project.



OR

Right Click on Test Project and click **Add**.



Give an appropriate name of the **Test Suite** in the pop-up as shown below and click **OK**.



3.2.2.2. Delete a Test Suite

Select a Test Suite and click to delete that Test Suite.



OR

Right Click on a particular Test Suite and click **Delete**.



3.2.2.3. Move Up or Move Down a Test Suite

Select a Test Suite and click or respectively to Move Up or Move Down that particular Test Suite.

OR

Right Click on Test Suite and click **Move Up** or **Move Down**.

3.2.2.4. Cut, Copy, Skip or Rename a Test Suite

Select a Test Suite and right click on it to Cut, Copy, Skip or Rename that Test Suite.



Describe Properties of a Test Suite

Select a Test Suite. Right click on it and select Properties.



[Note: *A Dialog Box as shown below will pop-up which will allow a user to describe Test Suite Name, Priority, Description (Optional) and Requirement Reference (Optional). User can also refer Properties Dialog Box to check details like* ***Created Date****,* ***Last Modified Date****,* ***Last Run Date*** *and* ***Status*** *of a particular Test Suite.*]



3.2.3. Steps to Add & Manage Test Cases & Test Scripts

3.2.3.1. Add a Test Case

Select the Test Suite as created in Step **3.2.1.1**and click to create a New **Test Case** within that Test Suite.



OR

Right click on the Test Suite and click **Add**.



Give an appropriate name of the **Test Case** in the pop-up as shown below and click **OK**.



3.2.3.2. Create Test Steps

Select a Test Case and click [+] button from the **Test Editor Section** to add Test Step.



OR

Right click on the blank area of Test Editor and click **Add**.



After adding a Test Step, add the necessary information to the Test Step in the following process:

Step 1: Add a Test Step.

Step 2: Select Test command to perform from the drop-down list.

Step 3: Select necessary Action, Object and Input Value in the corresponding row, depending on the testing scenario.

Step 4: Check/uncheck the option of the screenshot.

Step 5: Enter Description if necessary.

Step 6: Add Next Test Step.

Step 7: Repeat the process in the same manner to create a complete Test Script.

[**Note:** *Series of Test Steps is called Test Script.*]

[**Note:** *User can also create Test Scripts by Importing Test Script or by using the Recording function.*]

For more details, refer section - **Import Test Script** and **Record Test Script**

Sample Test Script to Log into Makemytrip.com without Password and Verify the Text

Step 1: Create Test Case under Test Suite.

Step 2: Name the Test Case **'Login'**.

Step 3: Add a Test Step and input serial number.

Step 4: Select the **'Open Page'** Test command.

Step 5: Add **'https://support.makemytrip.com/customersupports.aspx'** as Value in the corresponding row.

Step 6: Select Test commands as **'Input'**, Object **'UC1_email'** and add Value as '**test@test.com**'.

Step 7: Select Test commands as **'Click'** and add Object as **'plainpassword'** (plainpassword will attempt to login without password).

Step 8: Select Test commands as **'Click And Wait'** and Object as **'javascript:void(0);**

Step 9: Select Test commands as '**Highlight**' and Object as **'errormsg_password'** (this step will highlight error message for not entering the password while logging in).

Step 10: Select Test commands as **'Verify'** with Action as **'Text'** and place Value as **'Please enter your Password'**.



3.2.3.3. Manage Test Steps

Delete, Cut, Copy or **Move** the Test Steps by using the buttons on the **Test Editor** OR by right clicking on the Test Steps.



3.2.3.4. Add Toggle BreakPoint to a Test Step

Right click on a Test Step to put **Toggle BreakPoint** to that step.



[Note: *This function will automatically pause the execution once it reaches the pre-defined Test Step. This kind of function is useful when a website requires some manual input/intervention during execution. For e.g., Inserting a Captcha Code while filling a form in some websites.*]

3.2.3.5. Delete a Test Script

Select a Test Script and click to delete that Test Case.



OR

Right Click on a Test Script and click **Delete**.



3.2.3.6. Move Up or Move Down a Test Script

Select a Test Script and click or respectively to Move Up or Move Down that particular Test Script.



OR

Right Click on and click **Move Up** or **Move Down**.



3.2.3.7. Cut, Copy, Skip or Rename a Test Script

Select a Test Script and right click on it to Cut, Copy, Skip or Rename that Test Script.



3.2.3.8. Fork

Select a Test Case and right click on it to Fork. Fork function allows users to execute Test Cases on multiple browsers simultaneously from the same instance.



[***Note***: *Default multiple browser opens from the instance i.e. Mozilla Firefox.*]

3.2.3.9. Describe Test Script details in Properties

Select a Test Script. Right click on it and select Properties.



[Note: *A Dialog Box as shown below will pop-up which will allow a user to describe Test Script Name, Description (Optional) and Requirement Reference (Optional). User can also refer Properties Dialog Box to check details like* ***Created Date****,* ***Last Modified Date****,* ***Last Run Date*** *and* ***Status*** *of a particular Test Script.*]


Properties
Test Suite - Button Submit
Name
*
Button Submit
Priority
Medium
Description
Requirement Reference
Submit
Created on
Wednesday 24 Apr 2013 15:41 IST
Last Modified On
Thursday 19 Nov 2015 12:42 IST
Last Run Status
PASS
Last Run on
Thursday 19 Nov 2015 12:44 IST
OK
Cancel
Next
Previous

4. PROCESS OF CREATING, EXECUTING, REPORTING & MANAGING TESTS IN TESTINGWHIZ

4.1. Create, Record and Import Automation Test Scripts

There are three methods of generating Test Scripts. Let us understand each of these three ways of generating Test Scripts.

1. Creating Manually
2. Recording (Using Internal Browser and External Browser)
3. Importing

4.1.1. Create Test Automation Scripts Manually

To execute a test, create a Test Script under Test Suite.

Refer Section – **Steps to Add & Manage Test Scripts** understand the process of creating Test Scripts.

4.1.2. Record to Create Test Script Using Internal Browser

User can record test scripts to avoid creating scripts manually. Follow these simple steps to generate a test script by recording:

4.1.2.1. Switch On Recording

Click 

on the Tool Bar to switch on Recording on the browser of preference.

[**Note:** *The moment a user clicks on the Record button, it will turn* Red

.]

OR

Click **Recording** button on the **Welcome screen**.



4.1.2.2. Enter Browser Control

Enter the URL of the website to test (For e.g. www.google.com).



4.1.2.3. Start Recording

Click near the Browser Control to begin the execution process. TestingWhiz will open the website in the Test Editor section.



Perform the required function like search, fill contact form, etc. (For e.g., Search '**Hotels in New York**').



Test scripts will start getting generated simultaneously in the bottom left section as user performs function.


New
Open
Import
Export
Record
Execute
Next
Pause
Stop
Log a Defect
Email Report
Image Comparison
Database Comparison
Test Management Tool
*Test Project
*Objects
Test Project
New Test Suite
New Test Case
Test Editor
New Test Case
Test Command Action Object
1 Open Page
2 Input q
3 Click And Wait 2
4 Click And Wait New Y
Record
Browser Control
https://www.google.co.in/?gfe_rd=cr&ei=ac8bVbqHJfHI8AeA7YH4Cw&gws_rd=ssl#q=
Object Eye
ID rhscol xpath HTML/BODY/DIV/D
Name Tag DIV
deals now & save with our price match guarantee.
New York Hotels - Orbitz
www.orbitz.com › Hotels › United States › New York
Compare Hotels in New York. Book reservations for New York hotels, motels, and resorts, with thousands of reviews on ORBITZ. See our New York hotel deals, backed by our Low ...
Hotels in New York - Skyscanner
www.skyscanner.net/hotels/nyca/new-york-hotels.html
Looking for hotels in New York? Skyscanner compares the best travel sites to bring you the cheapest prices on your New York hotels – Skyscanner Hotels.
New York hotels - Telegraph
www.telegraph.co.uk/travel/hotel/36301/New-York-hotels.html
The best hotels in New York to suit all budgets, chosen by our experts, including luxury hotels and cheap hotels in locations near Times Square and Central Park ...
New York City Hotels - Cheap Hotel Deals | Travelocity
www.travelocity.com › Hotels › United States of America › New York
New York City Hotels and Accommodations - from inexpensive to luxury, boutique to antique, find your hotel | book online @ Travelocity.com.
Located Near The Harley Da
Factory Tour and Main Attrac
New York City, NY Ho
www.midtownhotelnyc.com
Book Our Brand New NYC H
Save Up To 25% Off Your St
New York City Hotel D
www.hgicentralparknyhotel
Modern Affordable Hotel w/F
Book A Package Deal & Save
See your ad here »
hotels in new york - Google Search

Open the required site from the search results (For e.g., http://www.travelocity.com).



Perform the necessary process further to complete the recording process.

[Note: *While recording the test steps, a user can any time click back* *or forward* *buttons to add previous and next steps in the test script respectively.*]

4.1.2.4. Switch off the Recording

Click on 

button to stop the recording once a user reaches the desired step(s).

The tool will automatically generate the script based on the steps followed during the recording process.

Here is the example of the test script generated by recording the process of searching '***Hotels in New York***' in www.google.com.



4.1.3. Record to Create Test Script Using External Browser

User can also generate Test Scripts by recording using external browser. Follow these simple steps to record using external browser.

4.1.3.1. Switch On Recording

Click 

the Drop-down below the Record button to switch on recording.

[**Note:** *TestingWhiz by default supports only Google Chrome for external recording.*]



[**Note:** *The moment a user switches on the Recording, it will turn* Red

.]

[**Note:** *A new incognito window will get opened on Google Chrome.*]


TestingWhiz External Rec
localhost:8095
TestingWhiz
Code Less, Test More
Start:
Enter the URL to start recording from
Go
This is the landing page for the external recorder. The same recording rules will apply here as those seen in the inbuilt recorder. Additionally, you will be able to record events inside Iframes. However, this recorder does NOT support recording of HTTPS sites.

4.1.3.2. Enter URL

Enter the URL of the website to test (For e.g. www.google.com).

Click Go near the Browser Control to begin the recording process. The website will be open the website in the external browser window.


TestingWhiz External Rec
localhost:8095
TestingWhiz
Code Less, Test More
Start: www.google.com
Go
This is the landing page for the external recorder. The same recording rules will apply here as those seen in the inbuilt recorder. Additionally, you will be able to record events inside Iframes. However, this recorder does NOT support recording of HTTPS sites.

Perform the required function like search, fill contact form, etc. (For e.g., Search '**Hotels in New York**').


Google
www.google.com
Search Images Maps Play YouTube News Gmail Drive More
Sign in
Google
India
hotel in new york
hotel in new york city
hotel in new york manhattan
hotel in new york
hotel in new york near times square
hotel in new york cheap
hotel in new york with jacuzzi in room
hotel in new york with free parking
hotel in new york near central park
hotel in new york chinatown
hotel in new york the great gatsby
Google Search
I'm Feeling Lucky
Advanced search
Language tools
Punjabi

Test Script will start getting generated in the bottom left section as you perform function. (For e.g., Search '**Hotels in New York'**).


hotel in new york - Google
www.google.com/search?ie=ISO-8859-1&hl=en-IN&source=hp&q=hotel+in+new+york&oq=hotel+in+new+york&gs_l=heirloom-hp.3..0l10.10672.16544.0.88257.19.1
Search Images Maps Play YouTube News Gmail Drive More
Sign in
Google
hotel in new york
Google SafeSearch is ON
Web Images Videos News Shopping Maps Books
About 1,040,000,000 results
Any time
Past hour
Past 24 hours
Past week
Past month
Past year
All results
Verbatim
Ads related to hotel in new york
New York City Hotels - Experience This Spectacular City
www.hilton.com/New_York
Book Your Trip With Hilton Today!
Hilton Hotels & Resorts has 1,029,903 followers on Google+
Waldorf Astoria New York
DoubleTree - Metropolitan
Millenium Hilton
Hilton - Manhattan East
500 Hotels in New York NY - Lowest Price Guarantee - booking.com
www.booking.com/New-York-Hotels
Book Your Hotel in New York NY
Hotels in New York, NY - Expedia.co.in
www.expedia.co.in/New_York_Hotels
Expedia Guarantees the Best Price. New York Hotels up to 50% Off.
New York - Hotels.com
www.hotels.com/de1506246/hotels-new-york-new-york/
Looking for Hotels in New York City? Save 50% Off on NYC hotels and Earn a Free Night with our Welcome Rewards Program at Hotels.com. Book a New York ...
Hotel Special Deals in New York - Cheap hotels New York - 5 star hotel in New York
New York City hotels - TripAdvisor
Ads
Hotel Offers for New York
www.amextravel.com/
Book Great Hotels with AMEX Travel
Get Lowest Hotel Rates -Guaranteed!
Hotels In New York
www.goibibo.com/New-York-Hotels
Flat 15% Off On Your Hotel Booking.
Use Promo Code HOTINTNY. Book Now!
New York Hotels from $119
www.travelzoo.com/NewYork
Find Discounts on Top Hotels Today.
Compare Rates at up to 50% Off!
767 Hotels in New York
www.makemytrip.com/New-York-Hotels
Upto 80% Off on Selected Hotels.
Guaranteed Best New York Deals!
Hotels In New York
www.cheaphotels.com/New_York
The Best New York Hotel Deals
Book Online & Save Up to 70%

Perform the necessary process further to complete the recording process.

4.1.3.3. Switch off the Recording

On reaching the desired point of recording the test steps, click on 

button to stop the recording.

The tool will automatically generate the script based on the steps followed during recording process.

In this case, we browsed 2 pages of Google search results for the Hotels in New York. Here's the script generated:



4.1.4. Import Test Script

Import Test Script is another feature that lets a user build test automation scripts. User can import script file in **Excel** or **.twiz** format by following below mentioned steps.

4.1.4.1. Import Test Project

Click

from the Tool Bar to import Test Script stored in .twiz file.



OR

Open File menu and click **Import Test Project**.



4.1.4.2. Import from Excel

Click

from the Tool Bar to import Test Script saved as .xlsx or .xls.



OR

Open File menu and click **Import from Excel**.



4.2. Execute Test Script

4.2.1. Select Browser

Click down arrow in the

to select the browser to execute the created/imported/recorded Test Script(s).



[**Note:** *If a user selects a browser that doesn't exist in the system, and if fallback browser flag from* ***Settings>Configuration>Execution*** *is selected then, TestingWhiz will fall back to another browser and execute the Test Script.*]

4.2.2. Run Test Script

Click

from the Tool Bar to execute a Test Script.



[**Note:** *Test Script will be executed in the default browser selected by the user.*]

[**Note:** *During execution, TestingWhiz will display the Active Screen of the website being tested.]*

4.3. Pause Test Execution

Click on

to Pause live execution of a Test Script.


TestingWhiz Enterprise - C:\Users\kdchhatbar\.whiz\temp\basic_element.twiz
File Edit Settings Tools Support Help
New Open Import Export Record Execute Next Pause Stop
Log a Defect Email Report
Image Comparison Database Comparison
Test Management Tool
*Test Proj... Data Table Methods *Objects
Test Project
Test Suite
Basic Element
Test Editor Outline Test Data
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Select Value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
Console
Progress : 27%
05-06-2015 09:22:15.581 [INFO] Playing test execution.
05-06-2015 09:22:27.993 [INFO] Opened the page http://testing-whiz.com/demoscripts/basic-element.html.
05-06-2015 09:22:28.190 [INFO] Verified Title Testingwhiz - Basic Element.
05-06-2015 09:22:31.832 [INFO] Typed Testing in input_text.

[**Note**: *Click on Pause button only when it has turned Green.*]

4.4. Stop Test Execution

Click on

to stop test execution.


TestingWhiz Enterprise - C:\Users\kdchhatbar\.whiz\temp\basic_element.twiz
File Edit Settings Tools Support Help
New Open Import Export Record Execute Next Pause Stop
Log a Defect Email Report
Image Comparison Database Comparison
Test Management Tool
Data Table Methods *Objects
Test Editor Outline Test Data
Test Project
Test Suite
Basic Element
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Select Value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
Console
Progress : 27%
05-06-2015 09:22:15.581 [INFO] Playing test execution.
05-06-2015 09:22:27.993 [INFO] Opened the page http://testing-whiz.com/demoscripts/basic-element.html.
05-06-2015 09:22:28.190 [INFO] Verified Title Testingwhiz - Basic Element.
05-06-2015 09:22:31.832 [INFO] Typed Testing in input_text.

4.5. Move to Next Step

Click

to move to the next step if any of the step contains Toggle Breakpoint from where the execution has been paused automatically.


TestingWhiz Enterprise - C:\Users\kdchhatbar\.whiz\temp\basic_element.twiz
File Edit Settings Tools Support Help
New Open Import Export Record Execute Next Pause Stop
Log a Defect Email Report
Image Comparison Database Comparison
Test Management Tool
*Test Proj... Data Table Methods *Objects
Test Editor Outline Test Data
Test Project
Test Suite
Basic Element
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Select Value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
Console
Progress : 9%
05-06-2015 09:22:48.877 [INFO] Selected index value option_select on Opel .
05-06-2015 09:22:50.193 [INFO] Verified Text Input button.
05-06-2015 09:22:51.321 [INFO] Clicked on reset.
05-06-2015 09:22:51.431 [INFO] Writing Basic element script in execution log.
05-06-2015 09:23:29.211 [INFO] Playing test execution.
05-06-2015 09:23:40.900 [INFO] Opened the page http://testing-whiz.com/demoscripts/basic-element.html.
05-06-2015 09:23:41.041 [INFO] Pausing test execution.

[**Note:** *Step 5 in the above screen contains Toggle Breakpoint where the execution has been paused automatically. Click on Next button will resume the testing to execute next step.*]

To learn more, kindly refer section – **Pause Test Execution** & **Toggle BreakPoint**

4.6. Check Progress and Execution Log

Check the progress and test execution log in the Console section exactly below the Test Editor.


Console
Progress : 36%
04-01-2015 05:59:01.726 [INFO] Playing test execution.
04-01-2015 05:59:14.707 [INFO] Opened the page http://testing-whiz.com/demoscripts/basic-element.html.
04-01-2015 05:59:14.856 [INFO] Verified Title Testingwhiz - Basic Element.
04-01-2015 05:59:19.260 [INFO] Typed Testing in input_text.
04-01-2015 05:59:23.095 [INFO] Typed Testing in input_password.
04-01-2015 05:59:23.264 [INFO] Pausing test execution.

4.6.1. Clear or Export Logs

Clear the summary/log of execution using button or Export the log using from the Console tab.

4.7. Test Report

At the end of the testing cycle, a report will be generated which will contain the test results along with the execution log. Test Report describes the actions performed and the results of the action.



4.7.1. Analyze Report

Scroll towards the right or click on the maximize button to view a detailed report of the test execution.



Click **Pass/Fail/Skip/Not Run** to view complete details of the test execution along with the time taken to complete each step.


TestingWhiz Enterprise - C:\Users\kdchhatbar\.whiz\temp\basic_element.twiz
File Edit Settings Tools Support Help
New Open Import Export Record Execute Next Pause Stop
Log a Defect Email Report
Image Comparison Database Comparison
Test Management Tool
Test Editor Test Data Outline Reports -Test Project
Previously executed reports:
Test Project
Date and Time : Wednesday 06 May 2015 09:29 IST
Pass Fail Skip Not Run
Home
Test Suite 26831 ms
Basic Element 26831 ms
No Operation Action Object Value Result Time Description
1 Open Page http://testing-whiz.com/democscripts/basic-element.html Pass 4803
2 Verify Title Testingwhiz - Basic Element Pass 201
3 Input input_text Testing Pass 3604
4 Input input_password Testing Pass 3404
5 Input input_textarea TestingWhiz™ is an Easy, Intuitive and Affordable Test Automation Solution based on a robust FAST® Automation Engine that uses effortless and intelligent recording techniques like Keyword-Driven Testing, Data Pass 7603

[Note: *The test reports will be stored in "C:\Users\<username>\.whiz\reports" on the user's machine.*]

4.8. Log a Defect

If a test case fails, log a defect using Bug Tracking Tool.

Step 1: Click Log a Defect from the Tool Bar. Select the Bug Tracking Tool and URL and click **Connect**.



Step 2: After the connection has been successful, select the Project Name from the drop-down on the right side.

Step 3: Now select the respective Test Case from the left pane.

[**Note:** *Details will be automatically populated in the form.*]

Step 4: Click **Submit**. A Ticket Number will be generated and the defect will be registered in the respective Bug Tracking Tool.



[**Note:** *This feature will function only if a user has set Bug Tracking Tool credentials in the Configuration section.*]

[**Note:** *After a user submits the defect once, Submit button will become disabled so as to prevent the user from submitting the same defect again as a duplicate.]*

4.9. Email Report

Email complete report of the executed test cases using the Email Report feature.

Step 1: Click

from the Tool Bar.

Step 2: Enter recipient's email id in the '**To**' field.

Step 3: Enter **Subject** and **Message Content** and click to send the report.



[**Note:** *This feature will function only if a user has set Email Preferences in the Configuration section.*]

5. KEYWORD-DRIVEN & DATA DRIVEN TESTING IN TESTINGWHIZ

5.1. Keyword-driven Testing

Using Keyword-driven testing approach, TestingWhiz separates much of the programming work of Test Automation from the actual Test Design. Testers or Test designers can write the test cases based on a set of keywords into a table. The test is executed using a driver that reads the keywords and executes the corresponding codes.

5.1.1. Setting up Keyword-driven Test Script

Step 1: Create a Test Suite under Test Project.

Step 2: Add a Test case.

Step 3: Select Test Command from the available test commands as a keyword which associates with the action to be performed.

Step 4: Add Value in the corresponding cell to perform the function.

Step 5: Complete the Test Script as per the steps mentioned in section **3.2.3**.

Sample Test Script to open – www.google.com
Step 1: Create a Test Suite under Test Project. **Step 2:** Add a Test case. **Step 3:** Go to Test command and pick the option '**Open Page**' from the dropdown. **Step 4:** Put www.google.com in '**Value**' column.



5.2. Data Driven Testing

Testing a particular module for various valid/invalid combinations of data sets is a vital requirement before QA can provide sign off for a particular test suite. Testing a module with positive, negative and random data set consumes time and effort. TestingWhiz lets a user test an application with a different set of input values and ensures that the application works as expected. This is particularly useful while running quick regression cycles.

5.2.1. Setting up Data-driven Test Script

Step 1: Click on Data table tab

Step 2: Add a new data table

Step 3: Specify the name of the data table

Step 4: Add the fields and the default input values to perform the test

Step 5: Add the data to the fields created manually or by importing data from an Excel file using the import button

Step 6: Once the fields and the default input values are defined, create a Test Script in the Test Project Section with a Test command that fetches data from the Data table

Sample Data Driven Test Script to Log in www.testing-whiz.com with different usernames and passwords
Create Data in Data table. **Step 1:** Add a new Data table in Data table tab. **Step 2:** Name the Data table as **'Login Data'**. **Step 3:** Add Fields as **'Username'** and **'Password'**. **Step 4:** Add different sets of usernames and passwords as data, manually or by importing an Excel file.



Create Test Script to Call/Fetch data created in the Data table.

Step 5: Add a Test Case and select Test command as **'Open Page'** and add Value as **'http://testing-whiz.com/demoscripts/place-holder.html'**.

Step 6: Add next step and select **'Loop Start' or 'Loop End' or 'Loop Continue' or 'Loop Break'** as Test command to loop the process of login with different usernames and passwords. Add Value as **'Login Data'** (from Data table) to fetch all the usernames and passwords stored in the Data table.

Step 7: Select Test command as **'Input'**, add Object as '**txtPass'** and insert **Value** as **'${LoginData.username}'**.

Step 8: Select Test command as **'Input'**, add Object as '**txtPass'** and insert **Value** as **'${LoginData.password}'**.

Step 9: Select Test command as **'Click And Wait'** and Object as **'btnLogin'** (To click and wait for login after each combination of usernames and passwords).

Step 10: Select Test command as **'Loop End'** (To try logging in with various usernames and passwords until the login is successful).


TestingWhiz Enterprise - C:\Users\kdchhatbar\.whiz\temp\data_table.twiz
File Edit Settings Tools Support Help
New Open Import Export Record Execute Next Pause Stop
Log a Defect Email Report
Image Comparison Database Comparison
Test Management Tool
Test Project Data Table *Objects
Test Project
Test Suite
Login
Test Editor Test Data Outline
Login
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Loop Start LoginData
3 Input txtUser ${LoginData.username}
4 Input txtPass ${LoginData.password}
5 Click And Wait btnLogin
6 Loop End
Test Command Methods Variable
Search
Break
Call Method
Capture
Check
Click
Click And Wait
Compare
Continue
Data Table
Database

6. IMPORTANT FUNCTIONS OF TESTINGWHIZ

6.1. Data Flow Diagram View/Outline view

TestingWhiz provides a unique representation of the Test Step(s) with **Outline** which encapsulates the complexity of the test case by displaying all the steps of a test case through a flow chart. Click on any of the steps opens its sub steps and its respective flow chart.



6.2. Object Eye

TestingWhiz features Object Eye which allows a user to view the properties of an object during test recording process. Details like the ID, Name, xpath and Tag of the object are displayed based on the selection at the time of recording the test steps.



6.3. Object Repository

Object Repository feature tracks and stores the objects and properties of the Test Script(s) that have been captured at the time of recording test steps. It keeps track of the object as per the modules followed by a user at the time of recording the test steps. The objects are displayed URL wise.


TestingWhiz Enterprise - C:\Users\kdchhatbar\.whiz\temp\data_table.twiz
File Edit Settings Tools Support Help
New Open Import Export Record Execute Next Pause Stop
Log a Defect
Email Report
Image Comparison
Database Comparison
Test Management Tool
Test Project Data Table *Objects
Search
Testingwhiz - Place Holder(http://testing-whiz.com/demoscrip
txtUser
txtPass
btnLogin
Test Command Methods Variable
Search
Break
Call Method
Capture
Check
Click
Click And Wait
Compare
Continue
Data Table
Database
Test Editor Test Data Outline Object Details
Object Properties
Alias txtUser
ID txtUser
Name txtUser
Class Name
Tag Type Text Box
Inner Html
Value
xpath HTML/BODY/DIV/DIV[3]/DIV/DIV/DIV[2]/FORM/TABLE/TBODY/TR/TD[2]/INPUT
Location
X Location 183 Width 262
Y Location 173 Height 31
Apply

Following are the attributes of an Object that are displayed in the Object Repository, according to URLs:

Alias	Alias by default displays the **Object Id** of the selected object which is utilized in the test step grid. [**Note**: *A user can change the Alias name. It is advisable to provide user-friendly names to test scripts for easy maintenance.*]
Id	Displays the **Id** of the selected object.
Name	Displays the **Name** of the selected object.
Class Name	Displays **Class Name** of the selected object.
Tag Type	Displays the **Name of the Control** that has been selected during the test case execution.
Inner HTML	Displays the **Inner Html** of the page.
Value	Displays the **Text Inserted** in the selected object.
xpath	Displays the **Location** of the object through HTML structure.

[Note: *User can delete an Object from Repository using right click option.*]

[**Note:** *The system displays only those objects that have been used by a user.*]

6.4. Methods

TestingWhiz provides a feature of grouping functions as Methods so that a user can use/execute that method in the Test Case/Script multiple times. This reduces the code size, saves time and increases maintainability of the Test Scripts.

The Methods function is highly useful if multiple Test Scripts include the same set of functions, or functions that are frequently used.

6.4.1. Process of Creating and Calling Method

Here's a complete process of creating and calling Methods:

Let us take an example of the process of Login into TestingWhiz application.

Step 1: Select the Test Steps from the existing Test Scripts to group as a single Method.

Step2: Copy the selected Test Steps using button from Test Editor Tab or Right Click option.



Step 3: Go to Methods Tab and click to add a new Method.

Step 4: Enter the **Name of the Method** - For e.g., 'Login' and the **Parameter Value** – For e.g., 'Data'.



Step 5: Paste the copied Test Steps in the new Method created; i.e., '**Login'**.


TestingWhiz Enterprise - C:\Program Files\TestingWhiz Enterprise Edition\scripts\TestingWhiz.twiz
File Edit Settings Tools Support Help
New Open Import Export Record Execute Next Pause Stop
Log a Defect Email Report
Image Comparison Database Comparison
Test Management Tool
Test Project Data Table *Objects
Test Project
Test Suite
Enterprise Edition
Community Edition
Test Command *Methods Variable
Search
Methods
Login
Test Editor Test Data Outline
Login
Test Command Action Object Value Screenshot Description
Add
Delete
Cut
Copy
Paste
Toggle Breakpoint
Move Up
Move Down


TestingWhiz Enterprise - C:\Program Files\TestingWhiz Enterprise Edition\scripts\TestingWhiz.twiz
File Edit Settings Tools Support Help
New Open Import Export Record Execute Next Pause Stop
Log a Defect Email Report
Image Comparison Database Comparison
Test Management Tool
Test Project Data Table *Objects
Test Project
Test Suite
Enterprise Edition
Community Edition
Test Command *Methods Variable
Search
Methods
Login
Test Editor Test Data Outline
Login
Test Command Action Object Value Screenshot Description
1 Click And Wait gender:on
2 Select Value option_select Opel
3 Click reset

Step 7: Create a New Test Case under Test Suite.



Step 8: Add a new Test Step and select Test command as '**Call Method**'.



Step 9: Click **Value** in the corresponding cell and select Call Method from the drop-down of available methods – in this case select '**Login**'.

Step 10: Enter Parameter Value and click **Save**.



Step 11: Add further steps to the Script if necessary.

Step 12: Execute the Test Script.

[**Note:** *User can add any number of Methods.*]
[**Note:** *Methods defined under a particular Test Suite cannot be used for any other Test Suite.*]

6.5. Image Comparison

TestingWhiz helps users to compare two images and record the difference at pixel level. TestingWhiz automatically converts a particular webpage into an image to carry out the comparison.

User can perform pixel by pixel Image Comparison in the following ways:

1. Image to Image Comparison
2. Image to URL Comparison
3. URL to URL Comparison

[**Note**: *TestingWhiz only supports Image File formats – 'png, jpg, bmp and gif'.*]

[**Note**: *TestingWhiz only supports Image comparison of same file extension.*]

6.5.1. How Image Comparison Works

Image Comparison functionality allows a user to capture images from the specified path in test commands and resize the captured images to *600x600*. Targeted images shows the difference in (%) value. Image comparison functionality will only compare the color between two source files.

Here's a step by step process of comparing images of Google's Different domain pages with google.com

Step 1: Create a **New Test Case** under a **Test Suite**

Step 2: Add a New Test Step as **Loop Start** in the Test Editor tab or Double click on **Loop Start** command under Test Commands tab.

Step 3: Enter **Google** as a Value

Step 4: Add a New Test Step as **Check** in the Test Editor tab or Double click on **Check** command under Test Commands tab.

Step 5: Enter **Image** as an Action

Step 6: Click to enter Source 1, Source 2 and Tolerance details in Compare Image Test Command dialog box.

Step 7: Enter '**${Google.URL}**' in **Source 1** box.

Step 8: Enter 'http://google.com' in **Source 2** box.

Step 9: Set up **Tolerance level** which user want to check the similarities in Tolerance box.

[**Note**: *Tolerance level will be in (%) value.*]



Step 10: Click on **Save** button to save the details.

Step 11: End the Test Case by adding a Test Step as **Loop End** or Double click on **Loop End** command under Test Commands tab.

Step 12: Execute Test Script in any browser.

Step 13: On completion of execution user can view detailed logs in generated report.

Step 14: Click 

to view the Image Comparison report.



Here a user can view **0.55%** variance between the two urls as shown in the report.

Step 15: Click "**View Source and Target Image**" to view the compared images.



Step 16: User can also view Target images in whiz folder. "**C:\Users\testingwhiz\.whiz**"

6.6. Fork

TestingWhiz offers a functionality of executing your recorded scripts in single machine or multiple machines and multiple browsers simultaneously. This feature is called Fork.

Forking can be used in two ways as follows:

A. Test Case Forking

B. Test Step Forking

Both these ways of forking works on a single machine and also can be achieved on multiple machines if a Hub server URL is provided in the configurations Window and Nodes are connected.

6.6.1. Test Case Forking

If a user wants Test Cases to be executed in a new instance of a browser, Forking Test Cases can be used.

Here's a complete process of Forking a Test Case

Step 1: Select a Test Case from the existing Test Scripts and right click on it.



Step 2: Click

to Fork the selected Test Case.



Step 3: Click 

to start execution of Test Script in any browser.





Test Script will be executed in two new instances of the selected browser from the same machine.

6.6.2. Test Step Forking

User can Fork Test Steps to execute them in different instances of a browser by using **Fork Start** and **Fork End** command.

Here's the complete process of Forking Test Steps:

Step 1: Open any existing Test Scripts in TestingWhiz.



Step 2: Enter **Fork Start** and **Fork End** Command at the start and at the end of the Test Script.

OR

Drag & Drop **Fork Start** and **Fork End** Test Commands from the Test Command search box.



Step 3: Click 

to start execution of Test Script in any browser.





Test Steps will be executed in two new instances of the selected browser from the same machine.

6.7. Mobile Test Execution

TestingWhiz offers a functionality of executing Test Scripts on Android and iOS devices.

Here's the complete process of performing Mobile Test Execution

Step 1: Select a default browser as '**Android**' or '**iOS**' from the Configuration menu under Settings.



OR

Select **'Android'** or **'iOS'** from the execution drop-down, while executing the Test Script.



6.7.1. Android Environment Setup for Mobile Test Execution

I. Setup on Android Device

Step 1: Go to Settings of the Android Device

Step 2: Enable Developer Options by tapping Build Number for 7 times under About Phone menu

Step 3: Enable USB Debugging and Stay Awake option under the Developer Options menu

II. Setup on Desktop PC

Step 1: Install Android SDK

Step 2: Install Appium Server

6.7.1.1. Process to Execute Test Cases on Android Simulator

Step 1: Create and start a new device by using AVD Manager.

Step 2: Start the Appium Server.

Step 3: Copy the Appium Server Address and Port Number

Step 4: Paste the copied Server Address and Port Number into Server URL field – TestingWhiz Settings>Configurations>Mobile Web Testing>Android



Step 5: Copy the Android Simulator Name.

Step 6: Paste the copied Simulator Name into Device Name field - TestingWhiz Settings>Configurations>Mobile Web Testing>Android



Step 7: Select the Browser from the Browser Name drop-down.

Step 8: Apply and Test the Connection.

Step 9: Close the Configuration Window.

Step 10: Execute the Test Case on Android Simulator.

6.7.1.2. Process to Execute Test Cases on a Real Android Device

Step 1: Connect a real Android device with the Desktop PC using a cable.

Step 2: Start the Appium Server.

Step 3: Copy the Appium Server Address and Port Number.

Step 4: Paste the copied Server Address and Port Number into Server URL field - TestingWhiz Settings>Configurations>Mobile Web Testing>Android.



Step 5: Press Shift + Right Click to open command prompt under Platform-tools folder of Android SDK.

Step 6: Run **'adb devices'** command and copy the **Device ID**.

Step 7: Paste the Device ID into Device Name field - **TestingWhiz Settings > Configurations > Mobile Web Testing > Android**.



Step 8: Select the Browser from the Browser Name drop-down.

Step 9: Apply and Test the Connection.

Step 10: Close the Configuration Window.

Step 11: Execute the Test Case on a real Android Device.

6.7.2. iPhone Environment Setup for Mobile Test Execution

I. Setup on iOS Device

Step 1: Go to Settings of the iOS Device

Step 2: Select Safari

Step 3: Select Web Inspector under Advanced menu

II. Setup on MAC System

Step 1: Install Apple XCode

Step 2: Install Appium (1.3.4) Server

6.7.2.1. Process to Execute Test Cases on iOS Simulator

Step 1: Create and start a new iOS Simulator Device by using XCode.

Step 2: Start the Appium Server.

Step 3: Copy the Appium Server Address and Port Number.

Step 4: Paste the copied Server Address and Port Number into Server URL field – TestingWhiz Settings>Configurations>Mobile Web Testing>iOS.



Step 5: Copy the iOS Simulator Name.

Step 6: Paste the copied Simulator Name into Device Name field - TestingWhiz Settings>Configurations>Mobile Web Testing>iOS



Step 7: Select the Browser from the Browser Name drop-down.

Step 8: Apply and Test the Connection.

Step 9: Close the Configuration Window.

Step 10: Execute the Test Case on iOS Simulator.

6.7.2.2. Process to Execute Test Cases on Real IOS Device

Step 1: Go to Application and Select **Appium**.

Step 2: Right Click on it and Click **Show Package Contents**.

Step 3: Select **resources >> node-modules >> appium >> build**.

Step 4: Copy **SafariLauncher.zip "Link"** to the above mentioned location.

Step 5: Start the Appium server with Device UDID Capability.

Step 6: Install **ios_webkit_debug_proxy from "Link"** and follow the steps mentioned in it.

Step 7: Open Terminal and execute **"ios_webkit_debug_proxy -c "UDID of Device: 27753" -d"** command.

Step 8: Connect a real iOS device with MAC PC.

Step 9: Start the **Appium Server**.

Step 10: Copy the **Appium Server Address** and **Port Number**.

Step 11: Paste the copied **Server Address** and **Port Number** into Server URL field - TestingWhiz Settings > Configurations > Mobile Web Testing > iOS.



Step 12: Specify the the Device Name from **'iOSDeviceName'** device - TestingWhiz Settings > Configurations > Mobile Web Testing > iOS.

Step 13: Select the Browser from the browser names drop-down.

Step 14: Apply and Test the Connection.

Step 15: Close the Configuration Window.

Step 16: Execute the Test Case on a real iOS Device.

[**Note:** *User needs to have following iOS environment as a pre-requisite to perform Mobile execution on real iOS devices.*

1. Mac OS: 10.9.5
2. XCode: 6.1.1
3. iOS - 7.1 or 8.1
4. Appium 1.3.4]

6.8. Data Cleansing via Data Validation

Data cleansing is the process of detecting and correcting (or removing) corrupt or inaccurate records from a set of data records or database originally caused by user entry errors, by corruption in transmission or storage or different data dictionary definitions of similar entities in different stores. Data cleansing ensures that all the data sets are consistent and can be used in a meaningful manner.

Here's the complete process of how to perform Data Cleansing in TestingWhiz:

6.8.1. How to Perform Data Cleansing

For performing Data Cleansing, a user needs to first set up Data Validation rules.

To set up data validation rules, follow the steps mentioned below:

Step 1: Click Settings > Configuration > Data Validation Rules.

Step 2: Select the rule to validate and clean the data.

[**Note:** *By default, TestingWhiz provides 9 Data Validation rules.*]

Refer Section – **Configuration** > **Data Validation Rules** to create more rules other than the default rules.

Step 3: Create a New Test Case under a Test Suite.

Step 4: Add a Test Command '**Clean' > 'Data Set'**

Step 5: Click **Value tab**.

[**Note:** *A new window will pop-up.*]

Step 6: Browse and **select the file of Database** which contains the junk data to perform the cleaning

Step 7: Specify the Delimiter to separate different columns of data set

Step 8: Check the option **'Consider first row as the header row'** to set first row as header if column headers are not specified explicitly

Step 9: Click **'Get Data'** to fetch all the column values of data set which populates the following

- **Column List:** This is the list of all the columns from your data set file.
- **Alias:** This dropdown populates all the rules from the Data Validation Rules setting, and each of these rules can be applied against the column they have been selected for.
- **Substitution if rule is broken:** User needs to specify a replacement string which would be replaced if any of the rule is broken against each column.

Step 10: Select the **'Target File'** location where the file after Data Cleaning needs to be saved.

Step 11: Specify **'Timeout'** according to the complexity and time taken to consume data set to replace all the fields. Number of rows is directly proportional to the time. Time is to be specified in milliseconds.



After execution TestingWhiz will create a file which has cleaned data ready for further use. All the data would be validated according to the rule applied.

6.9. Risk Based Testing

Risk Based Testing is a type of software testing in which functions and features are tested based on priority. It uses risk analysis to recognize proactive chances to take out or avoid defects through non-testing activities and to help users select which test activities to perform.

This kind of testing includes both mitigation (testing to give chances to decrease the likelihood of faults, especially high-impact faults) and contingency (testing to know a workaround to create the defects that do get past us less painful).

TestingWhiz enables a user to perform Risk Based Testing by defining the risks at the Test Case level. This gives a user the granular advantage to test even the critical & minute parts of your application.

Here's the complete process of performing Risk Based Testing

6.9.1. How to perform Risk Based Testing (RBT)

Step 1: Create a new **Test Case** under a Test Suite

Step 2: Right Click on the Test Case and open **'Properties'** to define the Priority from the drop-down for performing RBT.

(**Note:** *By default, priority will be set as Medium.*)



Step 3: Enable Risk Based Testing by going to **Settings** >> **Configuration** >> **Risk Based Testing** and check the option **'RBT enabled execution'**.

Step 4: Choose the **Priority** of the respective Test Case as High, Medium or Low by checking on the respective options and click **Apply** to enable the execution.

Step 5: Execute the testing of the Test Cases selected under Risk Based scenario based on their priorities on the browser of choice


Configuration
General
Execution
Mobile Web Testing
Report
Recording
Data Validation Rules
Screen
Mail
Database
FTP
TestingWhiz Grid
Bug Tracking Tool
Test Management Tool
Risk Based Testing
Install/Update
Risk Based Testing
RBT enabled execution
Prioritize Test Cases execution as per business requirements.
High
Medium
Low
Restore Defaults
Apply
OK
Cancel

6.10. Web Services Testing

A web service is a collection of open protocols and standards used for exchanging data between applications or systems. Software applications written in various programming languages and running on various platforms can use web services to exchange data over computer networks like the Internet in a manner similar to inter-process communication on a single computer.

TestingWhiz allows users to test **RESTful and SOAP** WebServices.

Here's the complete process of performing Web Services Testing with TestingWhiz™.

6.10.1. RESTful Web Services Testing

Step 1: Create a New Test Case under a Test Suite.

Step 2: Select Test Command '**Execute > Restful Web Service'** from the available Test Commands.

Step 3: Click **Value** tab.

[**Note:** *A new window will pop-up.*]

Step 4: Enter the URL of the Web Service.

Step 5: Select the type of **Method** supported by the RESTful URL from the drop-down.

Step 6: Specify the **Headers (if any)** in **Request Header** fields. User can also specify multiple Headers separated in multiline.

Step 7: Specify '**Request Body'** parameters. User can also specify multiple Request Body parameters separated in multiline.

Step 8: Enter the variable name in '**Target Response Code**' field to store the Response code after execution.

Step 9: Enter the variable name in '**Target Response Header**' field to store the Header Response after execution.

Step 10: Enter the variable name in '**Target Response Body**' field to store the Response Body after execution.

Step 11: Click Save.



Further, the user needs to parse message received as Target Response Body in REST Web Service.

Step 12: Select Test Command '**Parse > JSON Message**'.

Step 13: Click **Value** tab.

[**Note:** *A new window will pop-up.*]

Step 14: Enter the Source Variable in which JSON Expression needs to be evaluated

[**Note:** *User needs to specify the same variable value which was specified in the Response Body field of Execute > RESTful Web Service test command.*]

Step 15: Enter the JSON Expression to extract data from the JSON Response variable specified above. User can hover over the Help icon to get suggestions.

Step 16: Specify the **Target Variable** name to store the result of the JSON Expression after execution.

Step 17: Click **Save**.

6.10.2. SOAP Web Services Testing

Step 1: Create a New Test Case under a Test Suite.

Step 2: Select Test Command '**Execute > SOAP Web Service'** from the available Test Commands.

Step 3: Click **Value** tab.

[**Note:** *A new window will pop-up.*]

Step 4: Enter the WSDL of the SOAP Web Service.

Step 5: Validate the WSDL to get all the functions supported by the specified WSDL.

Step 6: Select the type of **Method** from the drop-down populated based on the specified WSDL.

Step 7: Specify the Request based on the Method selected. User can edit the parameters and XML Request text inside the Request field.

Step 8: Enter the variable name in '**Target Response Code**' field to store the Response code after execution.

Step 9: Enter the variable name in '**Target Response Header**' field to store the Header Response after execution.

Step 10: Enter the variable name in '**Target Response Body**' field to store the Response Body after execution.

Step 11: Click **Save**.



Further, user needs to parse message received as Target Response Body in SOAP Web Service.

Step 12: Select Test Command '**Parse > XML Message**'.

Step 13: Click **Value** tab.

[**Note:** *A new window will pop-up.*]

Step 14: Enter the Source Variable in which XPath needs to be evaluated

[**Note:** *User needs to specify the same variable value which was specified in the Response Body field of Execute > SOAP Web Service test command.*]

Step 15: Enter the XPath to extract data from the XML Response variable specified above. User can hover over the Help icon to get suggestions.

Step 16: Specify the **Target Variable** name to store the result of the XPath after execution.

Step 17: Click **Save**.

6.11. Execution via TestingWhiz CI Plugin

TestingWhiz allows users to execute Test Scripts on server via TestingWhiz CI plugins such as Jenkins or Hudson.

Here's the process of integrating Jenkins Server with TestingWhiz:

Step 1: Copy the TestingWhiz Plugin file.

Step 2: Paste the copied file into the **.jenkins folder** of TestingWhiz.

Step 3: Open Jenkins in the browser: **http://localhost:8080/** or **http://ipaddress:8080/**.

Step 4: Configure Jenkins and enter the Server address where the Jenkins is installed in TestingWhiz.

Step 5: Build a Free Style project.

Step 6: Click on **Add Build Step** and select TestingWhiz Script.



Step 7: Add the Test Script path.

Step 8: Specify the browser for your build by selecting one from the Browser drop-down.

Step 9: Enter a specific Test suite or Test case to exclusively execute inside the Test Object column or leave it blank to execute the entire script file (optional).

Step 10: Specify the interval time between two steps that is to be performed while execution (optional).



Step 11: Click **Server Start** from Tools drop-down of TestingWhiz.



Step 12: Test Script is ready to be executed via Jenkins server.

[**Note:** *To avail Jenkins integration functionality on your TestingWhiz, email at sales@testing-whiz.com.*]

6.12. Accessing DataTable Values Without Loop

TestingWhiz allows user to access Datatable Values without loop.

Syntax to access Datatable Value without loop in value column of TestingWhiz commands is as follows:

${tablename.columnname[index#]}

Here is the example which showcases how to access the command.

e.g. If a user wants to access 2nd row of employee 'Name' column of 'Employee' table then syntax will be:

${Employee.Name[2]}

6.13. Importing Data from Other Test Projects

TestingWhiz facilitates you to import Test Cases\Suites\Data\Methods from other Test Project.

Here's the process to import Test Data from another Test Project:

Step 1: Select **File**

Step 2: Click on **Import Test Data.** A pop up to select Test Project will appear.



Step 3: Click to select **.twiz** file of the Test Project.



Step 4: Click  to select the Test Object.



Step 5: Click  to select the Data Table.



Step 6: Click on  to select the Method.



Step 7: Click Finish to complete the process.

7. TEST COMMANDS IN TESTINGWHIZ

TestingWhiz supports more than **290+ Test Commands**, including conditional and looping Test Commands. These Test Commands help a user build effective and reliable Automation Test Scripts with least effort.

7.1. How to Add a Test Command

Once a Test Case in a Test Suite has been created, users can start adding Test Steps and necessary Test Commands to perform a particular function while executing that Test Case. There are 2 ways to add Test Command to a Test Case as mentioned below:

7.1.1. Drop-down List

TestingWhiz provides an easy way to add Test Command from the Drop-down list. To add Test Command via Drop-down list, follow these simple steps

7.1.1.1. Add a Test Step

Add a Test Step in the Test Editor section by clicking on icon above Test Editor



OR

Right click on the Test Editor Section and select Add



7.1.1.2. Select Test Command

After adding a Test Case, click on the corresponding Test Command cell and click on the arrow to select the Test Command from the Drop-down list.



7.1.2. Drag & Drop Test Command

User can Drag & Drop a desired Test Command from the Test Commands Tab to the Test Commands column in the Test Editor section. To add Test Command using Drag & Drop, perform the following steps

Step 1: Select an Test Command from the Test Commands tab

Step 2: Drag it towards the Test Editor

Step 3: Drop in the Test Commands column



7.1.3. Double Click Test Command

User can also add Test Command to a Test Case by double clicking a particular Test Command from the Test Commands tab. To add Test Command, simply select Test Command and double click on it.

7.2. How to Add an Action Corresponding to a Particular Test Command

Once the required Test Command to a Test Step has been added, a user needs to add the corresponding Action to that Test Command in order to execute that Test Step. Just like Test Command, a user can select Action in 2 ways:

7.2.1. Drop-down List

User can select an Action corresponding to a particular Test Command from the Drop-down list. To select an Action, follow the below mentioned steps:

Step 1: Add a Test Step

Step 2: Select an Test Command

Step 3: Click on the corresponding Action cell and select the Action from the Drop-down list.



Refer Section – **Add Test command** to learn how to add a test step and select test command before adding an Action.

7.2.2. Drag & Drop Action

User can also select an Action for a particular Test Command by using Drag & Drop.

To add an Action using Drag and Drop, follow these steps

Step 1: Select the Action

Step 2: Drag it towards the Test Editor

Step 3: Drop in the Test Commands column


TestingWhiz Enterprise - C:\Program Files\TestingWhiz Enterprise Edition\scripts\TestingWhiz.twiz
File Edit Settings Tools Support Help
New Open Import Export Record Execute Next Pause Stop
Log a Defect Email Report
Image Comparison Database Comparison
Test Management Tool
*Test Project Data Table *Objects
Test Editor Test Data Outline
Test Project
Test Suite
Enterprise Edition
Community Edition
Test Command Methods Variable
Search
Check
Text
Title
Checked
Enterprise Edition
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Select Value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
Text

7.2.3. Double Click Action

User can also add an Action corresponding to a particular Test Command by expanding a particular Test Command and double clicking on a particular Action in the Test Commands tab.

[Note: *Selecting an* Action *will auto-fill the Test Command column if a user has not selected the required Test Command before.*]

8. LIST OF TEST COMMANDS & CORRESPONDING ACTIONS

This chapter will briefly describe about all the available Test Commands in TestingWhiz and their corresponding Actions.

8.1. Break

Break test command allows users to break the loop of test case which is used for a particular scenario.


Test Editor
Test Data
Outline
Basic Element
| Test Command | Action | Object | Value | Screenshot | Description
1 | Open Page | | | http://testing-whiz.com...
2 | Verify | Title | | Testingwhiz - Basic Ele...
3 | Loop Start | | | Data
4 | Input | | input_text | Testing
5 | Input | | input_password | *******
6 | Input | | input_textarea | TestingWhiz™ is an Easy...
7 | Click And Wait | | gender:on |
8 | Click And Wait | | hobbies2 |
9 | Break | | |
10 | Perform | Select:value | option_select | Opel
11 | Check | Text | | Input button
12 | Click | | reset |
13 | Write Message To ... | | | Basic element script
14 | Loop End | | |

8.2. Call Method

Call Method test command allows users to call a user defined method. This command works in the similar manner as the method calling concept would work in other Programming Language.



8.3. Capture

8.3.1. Webscreen

Capture test command allows users to capture the entire web page of a given URL, and stores it as an image at a predefined storage location.


Test Editor
Test Data
Outline
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Select Value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
12 Capture Webscreen

8.3.2. Snapshot

This test command allows users to capture only the visible page screen of the monitor, and stores it as an image.



#	Test Command	Action	Object	Value	Screenshot	Description
1	Open Page			http://testing-whiz.com...	☐	
2	Verify	Title		Testingwhiz - Basic Ele...	☐	
3	Input		input_text	Testing	☐	
4	Input		input_password	*******	☐	
5	Input		input_textarea	TestingWhiz™ is an Easy...	☐	
6	Click And Wait		gender:on		☐	
7	Click And Wait		hobbies2		☐	
8	Select	Value	option_select	Opel	☐	
9	Check	Text		Input button	☐	
10	Click		reset		☐	
11	Write Message To ...			Basic element script	☐	
12	Capture	Snapshot			☐	

8.4. Check

Check test command allows users to check a set of actions performed by another user. It will stop the execution from the point where it fails. This is applicable to all the actions that are performed using Check test command.



8.4.1. Text

This action allows users to check whether a specified text is present on a page or not. The action will be performed for all the text on the page. The check will be performed by matching the case of the text value specified. Text with special symbols will not be considered. For e.g. "hello" will be considered different from HELLO. Check test command will stop the execution from the point where it fails.

8.4.2. Title

This action allows users to check whether the title of the page has a specified value or not. Check test command will stop the execution from the point where it fails.

8.4.3. Checked

This action allows users to check whether the checkbox is checked or selected. Check test command will stop the execution from the point where it fails.

8.4.4. Unchecked

This action allows users to check whether the checkbox is unchecked or de-selected. Check test command will stop the execution from the point where it fails.

8.4.5. Visible

This action allows users to check whether a specific object is visible on the page or not. Check test command will stop the execution from the point where it fails.

8.4.6. Invisible

This action allows users to check whether a specific object is invisible/hidden on the page or not. Check test command will stop the execution from the point where it fails.

8.4.7. Enabled

This action allows users to check whether the object (links, buttons etc.) is enabled on the page. Check test command will stop the execution from the point where it fails.

8.4.8. Disabled

This action allows users to check whether the object (links, buttons etc.) is disabled on the page. Check test command will stop the execution from the point where it fails.

8.4.9. Exists

This action allows users to check whether the object exists on a specified page or not. Check test command will stop the execution from the point where it fails.

8.4.10. Selected:value

This action allows users to check whether the option of a specified value is selected in the dropdown list.

8.4.11. Selected:index

This action allows users to check whether the option of a specified index is selected in the dropdown list.

8.4.12. Text:value

This action allows users to check whether the object has a specified value or not. This test command can also be utilized by taking value from the text box.

For e.g. when the values in the textbox are automatically populated from a database, a user can check/verify these values by taking id or object of the textbox.

8.4.13. Cookie

This action allows users to check whether the page contains a specified cookie or not. The result of the cookie's presence or absence will be reflected in the log that is generated for the Report of the Test Case.

8.4.14. Single Occurrence

This action allows users to check whether the value occurs only one time on the page or not. The Single Occurrence action will occur only on page contents. It will not include page title, header etc. Check test command will stop the execution from the point where it fails.

8.4.15. Text Ignore Case

This action allows users to check whether the text is present on the page irrespective of the case of the text. The check will be performed by ignoring the case of the text value specified. Text with special symbols will not be ignored.

For e.g. "hello" will be considered same as HELLO. The check will be performed on all the contents that are present in the form of the text like labels, links etc. Check test command will stop the execution from the point where it fails.

8.4.16. URL Reachable

This action allows users to check if a supplied URL in value column is a valid URL or not.

8.4.17. Image

This action allows users to compare two images with URL to URL, File to File and URL to file comparison. It will run as per the behavior of Check functionality, which includes following scenarios:

A. The check command will fail if tolerance power given is less than actual difference in images.

B. The check command will pass if tolerance power given is greater than actual difference in images.

8.5. Click

Click test command allows users to perform click on a particular object.


Test Editor
Test Data
Outline
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Perform Select:value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script

[**Note:** *This test command does not contain any Action.*]

8.6. Clean

Clean test command allows users to clean junk data which are fetched from raw data sources by validating through a set of rules.


Test Editor
Test Data
Outline
Basic Element
| Test Command | Action | Object | Value | Screenshot | Description
1 | Open Page | | | http://testing-whiz.com...
2 | Verify | Title | | Testingwhiz - Basic Ele...
3 | Input | | input_text | Testing
4 | Input | | input_password | *******
5 | Input | | input_textarea | TestingWhiz™ is an Easy...
6 | Click And Wait | | gender:on |
7 | Click And Wait | | hobbies2 |
8 | Select | Value | option_select | Opel
9 | Check | Text | | Input button
10 | Click | | reset |
11 | Write Message To ... | | | Basic element script
12 | Clean | Dataset | |

Refer Section – **6.8.1** to know more about how to perform Data cleansing.

8.7. Click and Wait

This action allows users to perform an action on an object and wait for a particular time before performing the next action.



#	Test Command	Action	Object	Value	Screenshot	Description
1	Open Page			http://testing-whiz.com...	☐	
2	Verify	Title		Testingwhiz - Basic Ele...	☐	
3	Input		input_text	Testing	☐	
4	Input		input_password	*******	☐	
5	Input		input_textarea	TestingWhiz™ is an Easy...	☐	
6	Click And Wait		gender:on		☐	
7	Click And Wait		hobbies2		☐	
8	Perform	Select:value	option_select	Opel	☐	
9	Check	Text		Input button	☐	
10	Click		reset		☐	
11	Write Message To ...			Basic element script	☐	

[**Note:** *This test command does not contain any Action.*]

8.8. Compare

This test command allows users to compare numerical values and give a Boolean result.


Test Editor
Test Data
Outline
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Perform Select:value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
12 Compare --Select--
--Select--
Equal to
Greater than
Greater than or equal to
Less than

8.8.1. Less than

This action allows users to test whether a value is less than another value.

8.8.2. Less than or equal to

This action allows users to test whether two numeric values are less than or equal to each other.

8.8.3. Greater than

This action allows users to test whether a value is greater than another value or not.

8.8.4. Greater than or equal to

This action allows users to test whether two numeric values are equal to each other.

8.8.5. Equal to

This action allows users to identify two values and return true if the values on both sides are equal to one another.

8.8.6. Not equal to

This action allows users to check if the value of two operands are equal or not.

8.8.7. Data Table

This action allows users to compare two Data Tables and return number of different rows in Data Table1 & Data Table2.



8.8.8. Between Range

This test command allows users to validate whether a number lies between the specified range.

[**Note:** *User needs to specify the Test Value, Range Start, Range End and Target Variable in the Value tab of this command.*]

8.9. Continue

Continue test command helps users to continue through the loop in which it is used.


Test Editor
Test Data
Outline
If Else_If Else
| Test Command | Action | Object | Value | Screenshot | Description
1 | Open Page | | | http://testing-whiz.com... | |
2 | Perform | Select:value | EmployeeType | Permanent | |
3 | Loop Start | | | Data | |
4 | Continue | | | | |
5 | Click And Wait | | hire:Later | | | Hire later if employee is a Contingent Work...
6 | Loop End | | | | |
7 | ElseIf | Selected:value | EmployeeType | Permanent | |
8 | Click And Wait | | hire:Never | | | Don't hire if employee is already hired per...
9 | Else | | | | |
10 | Click And Wait | | hire:Now | | | Otherwise look to hire now.

8.10. DataTable

8.10.1. Size

This action allows users to get the number of rows available in the specified datatable.

8.10.2. Row

This action allows users to get the entire data of a row in a variable, in which column values are separated by comma.


Test Editor
Test Data
Outline
Compare DataTables
Test Command Action Object Value Screenshot Description
1 Perform Set:globalvariable Initialize mismatch counter variable
2 Perform Set:globalvariable Initialize loop counter variable
3 Loop Start Datatable1 Loop through first data table as reference
4 If Compare Carry out straight comparison between tw...
5 Else
6 Math Add Increment mismatch count
7 End If
8 Math Add Increment counter for indexing in compari...
9 Loop End
10 Write Message To ... ${mismatch_cnt} differe... Print differences count in data tables
11 Data Table --Select--
--Select--
Get Row
Size

8.11. Database

This test command allows users to perform the database related queries like Select, Insert, Update and Delete.



[Note: *User needs to configure Database Preferences in the Settings menu under Configuration section.*]

8.11.1. Fetch

This action allows users to extract the data from database by performing the Select Query. The result of the Select Query will be stored either in the Target Variable or Target Data table or Target file depending on user selection.

[**Note:** *After selecting the Fetch action, user needs to click on* *icon in the Value column and mention* ***DB Alias, Select Query & Target selection*** *details in the dialog box as shown below*.]



DB Alias	**The Alias of the database.**
Select Query	The Select Query which needs to be executed in order to fetch data.
Single Result	Select Single Result to store output generated from the Select Query to targeted variable.
Result Set	Select Result Set to store output generated from the Select Query to Targeted data table.
File	Select File to store output generated from the Fetch command to a .csv file.
Target Variable	The name of the variable which would store the output generated from the Select Query
Target Data table	The name of the Data table which would store the output generated from the Select Query.
Target File	The name of the file which would store the output generated from the Fetch command.
Timeout (In milliseconds)	User can specify database timeout period in milliseconds to control script behavior better. Default Timeout would be 6000 millisecondS.

8.11.2. Query

This action allows users to manipulate the data stored in the database with the help of Insert, Update and Delete queries.

[Note: *After selecting the Query action, user needs to click on* *icon in the Value column and mention* ***DB Alias*** *and* ***Query*** *details in the dialog box as mentioned below.*]



DB Alias	**The Alias of the database.**
Query	Enter the Query which needs to be executed.
Timeout (In milliseconds)	User can specify database timeout period in milliseconds to control script behavior better. Default Timeout would be 6000 milliseconds.

8.11.3. Comparison

This action allows users to compare query to query, file to file as well as query to file. The result of the Comparison will be stored in the targeted variable.

[**Note:** *After selecting the* Comparison *action, user needs to click on* *icon in the Value column and mention* ***Source 1&2***, ***DB Alias***, ***Query & Target Variable*** *details in the dialog box as shown below*.]



Source 1	**Select "Query" or "File" to compare.**
Source 2	Select "Query" or "File" to compare.
DB Alias	The Alias of the database.
Query	Enter the Query which needs to be executed.
Target Variable	The name of the variable which would store the output generated from the Select Query.
Timeout (In milliseconds)	User can specify database timeout period in milliseconds to control script behavior better. Default Timeout would be 6000 milliseconds.

8.12. Delete

Delete test command allows users to delete Cookie[s] of a web page.


Test Editor
Test Data
Outline
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Perform Select:value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
12 Delete --Select--
--Select--
All Cookies
Cookie

8.12.1. All Cookies

This action allows users to delete all the cookies of all the web pages used.

8.12.2. Cookie

This action allows users to delete specific cookies of a web page.

8.13. Dynamic Input

Dynamic Input test command enables users to pass a dynamic value inside the script, through an input box and make use of it further inside the script.



8.14. Else

Else test command allows users to execute a step for an otherwise condition.


Test Editor
Test Data
Outline
If Else_If Else
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Perform Select:value EmployeeType Permanent
3 If Selected:value EmployeeType Contingent
4 Click And Wait hire:Later Hire later if employee is a Contingent Work...
5 ElseIf Selected:value EmployeeType Permanent
6 Click And Wait hire:Never Don't hire if employee is already hired per...
7 Else
8 Click And Wait hire:Now Otherwise look to hire now.
9 End If

[**Note:** *This test command does not contain any Action.*]

8.15. ElseIf

ElseIf test command allows users to execute another condition to be tested when all the other conditions of the loop above it are not satisfied.


Test Editor
Test Data
Outline
If Else_If Else
| Test Command | Action | Object | Value | Screenshot | Description
1 | Open Page | | | http://testing-whiz.com...
2 | Perform | Select:value | EmployeeType | Permanent
3 | If | Selected:value | EmployeeType | Contingent
4 | Click And Wait | | hire:Later | | Hire later if employee is a Contingent Work...
5 | ElseIf | Selected:value | EmployeeType | Permanent
6 | Click And Wait | | hire:Never | | Don't hire if employee is already hired per...
7 | Else
8 | Click And Wait | | hire:Now | | Otherwise look to hire now.
9 | End If
10 | If | Selected:value | EmployeeType | Contingent
11 | Click And Wait | | hire:Later | | Hire later if employee is a Contingent Work...
12 | ElseIf | Selected:value | EmployeeType | Permanent
13 | End If
Selected:value
Text
Text:value
Title
URL Reachable

8.15.1. Text

This action allows users to verify whether the specified text is present on a page or not. The action will be performed for all the text on the page. The check will be performed by matching the case of the text value specified. Text with special symbols will not be considered.

For e.g. "hello" will be considered different from HELLO.

8.15.2. Title

This action allows users to verify whether the title of a page has the specified value or not.

8.15.3. Checked

This action allows users to verify whether the checkbox is checked or selected.

8.15.4. Unchecked

This action allows users to verify whether the checkbox is unchecked or de-selected.

8.15.5. Visible

This action allows users to verify whether a specific object is visible on the page or not.

8.15.6. Invisible

This action allows users to verify whether a specific object is invisible/hidden on the page or not.

8.15.7. Enabled

This action allows users to verify whether the object (links, buttons etc.) is enabled on the page.

8.15.8. Disabled

This action allows users to verify whether the object (links, buttons etc.) is disabled on the page.

8.15.9. Selected:index

This action allows users to verify whether the option of a specified index is selected in the dropdown list.

8.15.10. Selected:value

This action allows users to verify whether the option of a specified value is selected in the dropdown list.

8.15.11. Text:value

This action allows users to verify whether an object has a specified value or not. This action can also be utilized by taking value from the text box.

For e.g. when values in the textbox are automatically populated from a database, user can check/verify these values by taking id or object of the textbox.

8.15.12. Exists

This action allows users to verify whether the object exists on the page or not.

8.15.13. Compare

This action allows users to perform comparison between two stings i.e. verify whether two strings are equal or not. The Compare action will take the case sensitivity of the Strings into consideration.

8.15.14. Compare Ignore Case

This action works in the similar manner as Compare action but with little enhancement. This action will ignore the case sensitivity of the Strings at the time of comparison.

8.15.15. isBlankOrNull

This action allows users to verify whether the value of a Variable is Null and not.

8.15.16. Contains

This action allows users to determine whether a string contains a given sub string.

8.15.17. URL Reachable

This action allows users to verify if a supplied URL in value column is a valid URL or not.

8.15.18. Image

This action allows users to compare two images with URL to URL, File to File and URL to file comparison. It will validate as per the behavior of ElseIf-not command.

8.15.19. Less than

This action allows users to test whether a value is less than another value.

8.15.20. Less than or equal to

This action allows users to test whether two numeric values are less than or equal to each other.

8.15.21. Greater than

This action allows users to test whether a value is greater than another value or not.

8.15.22. Greater than or equal to

This action allows users to test whether two numeric values are equal to each other.

8.15.23. Equal to

This action allows users to identify two values and returns true if the values on both sides are equal to one another.

8.15.24. Not equal to

This action allows users to check if the value of two operands are equal or not.

8.15.25. Between Range

This test command allows users to validate whether a number lies between the specified range.

[**Note:** *User needs to specify the Test Value, Range Start, Range End and Target Variable in the Value tab of this command.*]

8.16. ElseIf-Not

Elseif-Not test command allows users to execute a condition if the action mentioned is not satisfied.


Test Editor
Test Data
Outline
If Else_If Else
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Perform Select:value EmployeeType Permanent
3 If Selected:value EmployeeType Contingent
4 Click And Wait hire:Later Hire later if employee is a Contingent Work...
5 ElseIf Selected:value EmployeeType Permanent
6 Click And Wait hire:Never Don't hire if employee is already hired per...
7 Else
8 Click And Wait hire:Now Otherwise look to hire now.
9 End If
10 If Selected:value EmployeeType Contingent
11 Click And Wait hire:Later Hire later if employee is a Contingent Work...
12 ElseIf-Not Contains EmployeeType Permanent
13 End If
--Select--
Checked
Compare
Compare Ignore Case
Contains

8.16.1. Text

This action allows users to verify whether a specified text is present on a page or not. The action will be performed for all the text on the page. The check will be performed by matching the case of the text value specified. Text with special symbols will not be considered. For e.g. "hello" will be considered different from HELLO.

8.16.2. Title

This action allows users to verify whether the title of the page has a specified value or not.

8.16.3. Checked

This action allows users to verify whether the checkbox is checked or selected.

8.16.4. Unchecked

This action allows users to verify whether the checkbox is unchecked or de-selected.

8.16.5. Visible

This action allows users to verify whether a specific object is visible on the page or not.

8.16.6. Invisible

This action allows users to verify whether a specific object is invisible/hidden on the page or not.

8.16.7. Enabled

This action allows users to verify whether the object (links, buttons etc.) is enabled on the page.

8.16.8. Disabled

This action allows users to verify whether the object (links, buttons etc.) is disabled on the page.

8.16.9. Selected:index

This action allows users to verify whether the option of a specified index is selected in the dropdown list.

8.16.10. Selected:value

This action allows users to verify whether the option of a specified value is selected in the dropdown list.

8.16.11. Text:value

This action allows users to verify whether an object has a specified value or not. This test command can also be utilized by taking value from the text box.

For e.g. when values in the textbox are automatically populated from a database, user can check/verify these values by taking id or object of the textbox.

8.16.12. Exists

This action allows users to verify whether the object exists on a page or not.

8.16.13. Compare

The Compare action allows users to perform the Comparison between two stings i.e. verify whether two strings are equal or not. The Compare action will take the case sensitivity of the Strings into consideration.

8.16.14. Compare Ignore Case

The Compare Ignore Case action will work in the similar manner as Compare action but with little enhancement. This action will ignore the case sensitivity of the Strings at the time of comparison.

8.16.15. IsBlankOrNull

The isBlankOrNull Test command enables users to verify whether the value of a Variable is Null and not.

8.16.16. Contains

The Contains action allows users to determine whether a string contains a given sub string.

8.16.17. URL Reachable

This action allows users to verify if a supplied URL in value column is a valid URL or not.

8.16.18. Image

This action allows users to compare two images with URL to URL, File to File and URL to file comparison. This command will validate as per the behavior of ElseIf-not command.

8.16.19. Less than

This action allows users to test whether a value is less than another value.

8.16.20. Less than or equal to

This action allows users to test whether two numeric values are less than or equal to each other.

8.16.21. Greater than

This action allows users to test whether a value is greater than another value or not.

8.16.22. Greater than or equal to

This action allows users to test whether two numeric values are equal to each other.

8.16.23. Equal to

This action allows users to identify two values and returns true if the values on both sides are equal to one another.

8.16.24. Not equal to

This action allows users to check if the value of two operands are equal or not.

8.16.25. Between Range

This test command allows users to validate whether a number lies between the specified ranges.

[**Note:** *User needs to specify the Test Value, Range Start, Range End and Target Variable in the Value tab of this command.*]

8.17. End If

End If test command allows users to end the loop of If conditions.


Test Editor
Test Data
Outline
If Else_If Else
| Test Command | Action | Object | Value | Screenshot | Description
1 | Open Page | | | http://testing-whiz.com... | |
2 | Perform | Select:value | EmployeeType | Permanent | |
3 | If | Selected:value | EmployeeType | Contingent | |
4 | Click And Wait | | hire:Later | | | Hire later if employee is a Contingent Work...
5 | ElseIf | Selected:value | EmployeeType | Permanent | |
6 | Click And Wait | | hire:Never | | | Don't hire if employee is already hired per...
7 | Else | | | | |
8 | Click And Wait | | hire:Now | | | Otherwise look to hire now.
9 | End If | | | | |

[**Note:** *This test command does not contain any Action.*]

8.18. Enter Authentication

Enter Authentication test command allows users to provide authentication on a given application. This can prevent unauthorized access of applications.


Test Editor
Test Data
Outline
If Else_If Else
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Perform Select:value EmployeeType Permanent
3 If Selected:value EmployeeType Contingent
4 Click And Wait hire:Later Hire later if employee is a Contingent Work...
5 ElseIf Selected:value EmployeeType Permanent
6 Click And Wait hire:Never Don't hire if employee is already hired per...
7 Else
8 Click And Wait hire:Now Otherwise look to hire now.
9 End If
10 Enter Authenticati...

8.19. Execute

Execute test command allows users to execute a particular script.

8.19.1. JavaScript

This action allows users to execute JavaScript through a simple JavaScript code.

8.19.2. RESTful Web Service

This command allows users to test RESTful Web Services with a single test command, and store results in a variable.

Refer Section – **6.10.1** to know more about how to perform RESTful Web Services Testing.

8.19.3. SOAP Web Service

This command allows users to test SOAP Web Services with a single test command, and store results in a variable.


Test Editor
Test Data
Outline
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Select Value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
12 Execute --Select--
--Select--
Javascript
Rest Web Service
SOAP Web Service

Refer Section – **6.10.2** to know more about how to perform RESTful Web Services Testing.

8.20. Exit

Exit test command allows users to exit from current Test Case/Test Suite/Test Project.



8.20.1. Test Case

This action allows users to exit from a Test Case and switch to the next consecutive Test Case.

8.20.2. Test Project

This action allows users to exit from a Test Project and switch to the next consecutive Test Project.

8.20.3. Test Suite

This action allows users to exit from a Test Suite and switch to the next consecutive Test Suite.

8.21. Export To

The Export to test command enables users to export the data stored in Data tables to .XML and .CSV file.



8.21.1. XML

The XML action enables users to export the data into the .XML file format.

[**Note:** *After selecting the CSV action, user needs to provide* ***Target File*** *in .CSV format in which the exported file should be stored and also provide Source Data table details as shown below.*]



8.21.2. CSV

The CSV action enables users to export the data into the CSV file format.

[**Note:** *After selecting the CSV action, user needs to provide* ***Target File*** *in .CSV format in which the exported file should be stored and also provide* ***Source Data table*** *details as shown below.*]



8.22. FTP

FTP command allows users to integrate and access FTP file / server for testing



8.22.1. Upload

This action allows users to upload a local file to FTP server.

8.22.2. Is Exist

This action allows users to validate the presence of the specified file on FTP server.

8.22.3. Download

This action allows users to download a file from the FTP server to local machine.

8.22.4. Delete

This action allows users to delete a file from the FTP server.

8.23. Fail

Fail test command allows users to define failure of a Test Step/Test Case manually.


Test Editor
Test Data
Outline
Javascript Submit
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Input name Test Name
3 Input address Test Address
4 Input City Test City
5 Input E-mail test@email.com
6 Click And Wait why:Dunno
7 Perform Select:value refer Through WDF
8 Click And Wait potatoes
9 Fail

8.24. Fork End

This command allows users to End command.


Test Editor
Test Data
Outline
String Operation
| Test Command | Action | Object | Value | Screenshot | Description
1 | Open Page | | | http://testing-whiz.com...
2 | Fork Start
3 | Perform | Set:variable
4 | Perform | Set:variable
5 | Input | | oldPassword | ${varOldPassword}
6 | Input | | newPassword | ${varNewPassword}
7 | Click | | checkSubmitB...
8 | If | Compare
9 | Get | Text | alert | alertText
10 | String | Compare
11 | End If
12 | String | Length
13 | Write Message To ... | | | ${varLength}
14 | Fork End

[**Note:** *This test command does not contain any Action.*]

8.25. Fork Start

This command allows users to Start command.



[**Note:** *This test command does not contain any Action.*]

8.26. Get

Get test command allows users to fetch/get the attribute of an object, table row count, table column count, table cell data.

[**Note:** *User has to use a variable to store the fetched value and display it on the report*.]



8.26.1. Text

Text action allows users to get the text of a textbox.

8.26.2. Value

This action allows users to get the value of any object.

8.26.3. Table Row Count

This action allows users to get the total row count of a particular table.

8.26.4. Table Column Count

This action allows users to get the total column count of a particular table.

8.26.5. Attribute

This action allows users to get any attribute of an object.

8.26.6. Table Cell Data

This action allows users to get data of a particular table cell.

8.26.7. Title

Title action allows users to get the Title of a particular website or URL.

8.26.8. Current Page URL

Current Page URL action allows users to get the URL of the current website.

8.26.9. Alert Text

This action allows users to get the Text value of an Alert Pop-up.

8.26.10. Page Source

This action allows users to extract the source of the current URL which is opened in browser.

8.26.11. Table

This action allows users to extract the entire data of the specified table object into Datatable.

8.26.12. Elements

This action allows users to get elements of particular type from the specified web page and allows to store to Datatable.

8.27. Highlight

Highlight test command allows users to highlight a particular object in a page.


Test Editor
Test Data
Outline
Javascript Submit
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Input name Test Name
3 Input address Test Address
4 Input City Test City
5 Input E-mail test@email.com
6 Click And Wait why:Dunno
7 Perform Select:value refer Through WDF
8 Click And Wait potatoes
9 Highlight address

[**Note:** *This test command does not contain any Action.*]

8.28. If

If test command allows users to check for specific conditions before executing a test step.



8.28.1. Text

This action allows users to verify whether the specified text is present on a page or not. The action will be performed for all the text on the page. The check will be performed by matching the case of the text value specified. Text with special symbols will not be considered. For e.g. "hello" will be considered different from HELLO.

8.28.2. Title

This action allows users to verify whether the title of the page has the specified value or not.

8.28.3. Checked

This action allows users to verify whether the checkbox is checked or selected.

8.28.4. Unchecked

This action allows users to verify whether the checkbox is unchecked or de-selected.

8.28.5. Visible

This action allows users to verify whether a specific object is visible on the page or not.

8.28.6. Invisible

This action allows users to verify whether a specific object is invisible/hidden on the page or not.

8.28.7. Enabled

This action allows users to verify whether the object (links, buttons etc.) is enabled on the page.

8.28.8. Disabled

This action allows users to verify whether the object (links, buttons etc.) is disabled on the page.

8.28.9. Selected:index

This action allows users to verify whether the option of the specified index is selected in the dropdown list.

8.28.10. Selected:value

This action allows users to verify whether the option of the specified value is selected in the dropdown list.

8.28.11. Text:value

This action allows users to verify whether an object has the specified value or not. This test command can also be utilized by taking value from the text box.

For e.g. when values in the textbox are automatically populated from a database, user can check/verify these values by taking id or object of the textbox.

8.28.12. Exists

This action allows users to verify whether the object exists on the page or not.

8.28.13. Compare

The Compare action users to perform the Comparison between two stings i.e. verify whether two strings are equal or not. The Compare action will take the Case Sensitivity of the Strings into consideration.

8.28.14. Compare Ignore Case

The Compare Ignore Case action will work in the similar manner as Compare action but with little enhancement. This action would ignore the Case Sensitivity of the Strings at the time of comparison.

8.28.15. IsBlankOrNull

The isBlankOrNull Test command allows users to verify whether the value of a Variable is Null and not.

8.28.16. Contains

The Contains action allows users to remove the leading and trailing blanks in the String.

8.28.17. URL Reachable

This action allows users to verify if a supplied URL in value column is a valid URL or not.

8.28.18. Image

This action allows users to compare two images with URL to URL, File to File and URL to file comparison.

This command will validate as per the behavior of If command.

8.28.19. Less than

This action allows users to test whether a value is less than another value.

8.28.20. Less than or equal to

This action allows users to test whether two numeric values are less than or equal to each other.

8.28.21. Greater than

This action allows users to test whether a value is greater than another value or not.

8.28.22. Greater than or equal to

This action allows users to test whether two numeric values are equal to each other.

8.28.23. Equal to

This action allows users to identify two values and returns true if the values on both sides are equal to one another.

8.28.24. Not equal to

This action allows users to check if the value of two operands are equal or not.

8.28.25. Between Range

This test command allows users to validate whether a number lies between the specified range.

[**Note**: *User needs to specify the Test Value, Range Start, Range End and Target Variable in the Value tab of this command*.]

8.29. If-Not

If-Not test command allows users to check for conditions before executing a test step.


Test Editor
Test Data
Outline
If Else_If Else
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Perform Select:value EmployeeType Permanent
3 If Checked EmployeeType
4 Click And Wait hire:Later Hire later if employee is a Contingent Work...
5 ElseIf Selected:value EmployeeType Permanent
6 Click And Wait hire:Never Don't hire if employee is already hired per...
7 Else
8 Click And Wait hire:Now Otherwise look to hire now.
9 End If
10 If-Not --Select-- EmployeeType
11 Click And Wait hire:Later Hire later if employee is a Contingent Work...
12 End If
--Select--
Checked
Compare
Compare Ignore Case
Contains

8.29.1. Text

This action allows users to verify whether the specified text is present on a page or not. The action will be performed for all the text on the page. The check will be performed by matching the case of the text value specified. Text with special symbols will not be considered. For e.g "hello" will be considered different from HELLO.

8.29.2. Title

This action allows users to verify whether the title of the page has the specified value or not.

8.29.3. Checked

This action allows users to verify whether the checkbox is checked or selected.

8.29.4. Unchecked

This action allows users to verify whether the checkbox is unchecked or de-selected.

8.29.5. Visible

This action allows users to verify whether a specific object is visible on the page or not.

8.29.6. Invisible

This action allows users to verify whether a specific object is invisible/hidden on the page or not.

8.29.7. Enabled

This action allows users to verify whether the object (links, buttons etc.) is enabled on the page.

8.29.8. Disabled

This action allows users to verify whether the object (links, buttons etc.) is disabled on the page.

8.29.9. Selected:index

This action allows users to verify whether the option of the specified index is selected in the dropdown list.

8.29.10. Selected:value

This action allows users to verify whether the option of the specified value is selected in the dropdown list.

8.29.11. Text:value

This action allows users to verify whether an object has the specified value or not. This test command can also be utilized by taking value from the text box. For e.g. when values in the textbox are automatically populated from a database, user can check/verify these values by taking id or object of the textbox.

8.29.12. Exists

This action allows users to verify whether the object exists on the page or not.

8.29.13. Compare

The Compare action allows users to perform the Comparison between two stings i.e. verify whether two strings are equal or not. The Compare action will take the Case Sensitivity of the Strings into consideration.

8.29.14. Compare Ignore Case

The Compare Ignore Case action will work in the similar manner as Compare action but with little enhancement. This action would ignore the Case Sensitivity of the Strings at the time of comparison.

8.29.15. IsBlankOrNull

The isBlankOrNull Test command allows users to verify whether the value of the Variable is Null and not.

8.29.16. Contains

The Contains action allows users to remove the leading and trailing blanks in the String.

8.29.17. URL Reachable

This action allows users to verify if a supplied URL in value column is a valid URL or not.

8.29.18. Image

This action allows users to compare two images with URL to URL, File to File and URL to file comparison. This command will validate as per the behavior of If – not command.

8.29.19. Less than

This action allows users to test whether a value is less than another value.

8.29.20. Less than or equal to

This action allows users to test whether two numeric values are less than or equal to each other.

8.29.21. Greater than

This action allows users to test whether a value is greater than another value or not.

8.29.22. Greater than or equal to

This action allows users to test whether two numeric values are equal to each other.

8.29.23. Equal to

This action allows users to identify two values and returns true if the values on both sides are equal to one another.

8.29.24. Not equal to

This action allows users to check if the value of two operands are equal or not.

8.30. Input

Input test command allows users to set a particular value in a textbox.



#	Test Command	Action	Object	Value	Screenshot	Description
1	Open Page			http://testing-whiz.com...	☐	
2	Verify	Title		Testingwhiz - Basic Ele...	☐	
3	Input		input_text	Testing	☐	
4	Input		input_password	*******	☐	
5	Input		input_textarea	TestingWhiz™ is an Easy...	☐	
6	Click And Wait		gender:on		☐	
7	Click And Wait		hobbies2		☐	
8	Perform	Select:value	option_select	Opel	☐	
9	Check	Text		Input button	☐	
10	Click		reset		☐	
11	Write Message To ...			Basic element script	☐	

[**Note:** *This test command does not contain any Action.*]

8.31. IsSorted

This command allows users to perform following actions.

[**Note**]: It would work for strings, numeric data & alphanumeric data. For dates and other things, string based comparison will be made.



8.31.1. Ascending

This action allows users to validate sorting in ascending manner of the specified column of a datatable.

8.31.2. Descending

This action allows users to validate sorting in Descending manner of the specified column of a datatable.

8.32. KeyPress

Keypress test command allows users to perform functionalities of various function keys on a web page.



8.32.1. Enter

This action allows users to perform the functionality of an Enter key on an object.

8.32.2. Escape

This action allows users to perform the functionality of an Escape key on an object. User can use this object when they want to escape an alert/message box or any frame/window.

8.32.3. Tab

This action allows users to use the functionality of the Tab key. It will move to the object whose id is defined in the Object column.

8.32.4. Refresh

This action allows users to Refresh and re-load the contents of the web page.

8.32.5. F1

This action allows users to view the Help contents of an application.

8.32.6. F3

This action allows users to access the Search box on the web page.

8.32.7. F6

This action allows users to Move the cursor to the URL bar of the web page.

8.32.8. F10

This action allows users to Move the cursor to the first Menu in the Menu Bar of the web page.

8.32.9. F11

This action allows users to view the Full-screen of a web page. It will hide the URL bar, menu bar, tabs of the web page.

8.32.10. Page Up

This action allows users to use the functionality of Page Up key. It scrolls the page up in the same proportion as the Page Up key functions.

8.32.11. Page Down

This action allows users to use the functionality of Page Down key. It scrolls the page down in the same proportion as the Page Down key functions.

8.32.12. Up

This action allows users to use the functionality of up key wherever scrolling is required on a page. It will move to the object whose id is defined in the Object column.

8.32.13. Down

This action allows users to use the functionality of down key wherever scrolling is required on a page. It will move to the object whose id is defined in the Object column.

8.32.14. Left

This action allows users to use the functionality of Left key. It will move to the object whose id is defined in the Object column.

8.32.15. Right

This action allows users to use the functionality of Right key. It will move to the object whose id is defined in the Object column.

8.33. Loop End

Loop End test command allows users to end a defined loop of test steps. To execute a loop, user needs to configure it using Data table.


Test Editor
Test Data
Outline
Basic Element
| Test Command | Action | Object | Value | Screenshot | Description
1 | Open Page | | | http://testing-whiz.com... |
2 | Loop Start | | | Data |
3 | Verify | Title | | Testingwhiz - Basic Ele... |
4 | Input | | input_text | Testing |
5 | Input | | input_password | ******* |
6 | Input | | input_textarea | TestingWhiz™ is an Easy... |
7 | Click And Wait | | gender:on | |
8 | Click And Wait | | hobbies2 | |
9 | Perform | Select:value | option_select | Opel |
10 | Check | Text | | Input button |
11 | Click | | reset | |
12 | Loop End | | | |

[**Note:** *This test command does not contain any Action*.]

8.34. Loop Start

Loop Start test command allows users to start a defined loop of test steps. To execute a loop, user needs to configure it using Data table.

[**Note:** *User needs to provide details of Target Data Table, Start Index and End Index*. Also, user can choose between Standard and Custom Loop based on the requirements]

8.35. Math

The Math Test command allows users to perform calculation on numeric data by formatting it in a desired format.



8.35.1. Absolute Value

The action allows users to return the absolute value of a double value. If the argument is not negative, the argument is returned. If the argument is negative, the negation of the argument is returned.

In Special cases: If the argument is positive zero or negative zero, the result is positive zero. If the argument is infinite, the result is positive infinity. If the argument is Nan, the result is Nan.]

8.35.2. Integer Value

The Integer action allows users to return the value of this double as an integer (by casting to type integer).

8.35.3. Floor Value

The Floor action allows users to return the largest (closest to positive infinity) double value that is less than or equal to the argument and is equal to a mathematical integer.

In Special cases: If the argument value is already equal to a mathematical integer, then the result is the same as the argument. If the argument is Nan or an infinity or positive zero or negative zero, then the result is the same as the argument.

8.35.4. Ceiling Value

The Celling action allows users to return the smallest (closest to negative infinity) double value that is greater than or equal to the argument and is equal to a mathematical integer.

In Special cases: If the argument value is already equal to a mathematical integer, then the result is the same as the argument. If the argument is Nan or an infinity or positive zero or negative zero, then the result is the same as the argument. If the argument value is less than zero but greater than -1.0, then the result is negative zero.

8.35.5. Add

The Add action returns the sum of supplied values, or variables, to the user.

8.35.6. Subtract

The Subtract action returns the difference of supplied values or variables, to the user.

8.35.7. Random Number

This action allows users to generate a random integer within the limits of Minimum & Maximum Value and store it in a variable.

8.36. Move

Move test command allows users to move to a specific page/frame/window.



8.36.1. To Next Page

This action allows users to move to the next page after the current page.

8.36.2. To Previous Page

This action allows users to move to the previous page.

8.36.3. To Window

This action allows users to move the focus to any open window on a web page.

8.36.4. To Frame

This action allows users to move to different frames of the framework-design based web page.

8.36.5. To Parent

This action allows users to move to parent window/web page from any opened window/web page.

8.37. Open Page

Open Page test command allows users to open a particular web page in the browser.


Test Editor
Test Data
Outline
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Perform Select:value option_select Opel
9 Check Text Input button
10 Click reset

[**Note:** *This Test command does not contain any Action*.]

8.38. Parse

8.38.1. JSON Message

This command allows users to parse any JSON string or the JSON string which is returned as a result in REST Web Service test command.

For example:

```
"store": {
      "book": [
         {
            "category": "reference",
            "author": "Nigel Rees",
            "title": "Sayings of the Century",
            "price": 8.95
         },
         {
            "category": "fiction",
            "author": "Evelyn Waugh",
            "title": "Sword of Honour",
            "price": 12.99
         },
         {
            "category": "fiction",
            "author": "Herman Melville",
            "title": "Moby Dick",
            "isbn": "0-553-21311-3",
            "price": 8.99
         },
}
```

"store.book[*].author" expression will fetch all the authors of all books.

"book[2]" expression will fetch the third book from the list.

"book[(@.length-1)]" expression will fetch the last book.

8.38.2. XML Message

This test command allows users to extract some values from an XML message. XML messages are the result of SOAP Webservices responses. For example: User can mousehover on the Help icon available.

For example:

```
<soap:Envelopexmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"                    [^]
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" [^] xmlns:xsd="http://www.w3.org/2001/XMLSchema"> [^]
   <soap:Body>
      <GetCityForecastByZIPResponse xmlns="http://ws.cdyne.com/WeatherWS/"> [^]
         <GetCityForecastByZIPResult>
            <Success>true</Success>
            <ResponseText>City Found</ResponseText>
            <State name="a">FL</State>
            <City>Mid Florida</City>
            <WeatherStationCity>Orlando</WeatherStationCity>
            <ForecastResult>
               <Forecast>
                  <Date>2014-08-18T00:00:00</Date>
                  <WeatherID>2</WeatherID>
                  <Desciption>Partly Cloudy</Desciption>
```

```
                <Temperatures>
                   <MorningLow/>
                   <DaytimeHigh>95</DaytimeHigh>
                </Temperatures>
                <ProbabilityOfPrecipiation>
                   <Nighttime/>
                   <Daytime>30</Daytime>
                </ProbabilityOfPrecipiation>
             </Forecast>
          </ForecastResult>
       </GetCityForecastByZIPResult>
    </GetCityForecastByZIPResponse>
 </soap:Body>
</soap:Envelope>
```

XPath :

Get State value : //GetCityForecastByZIPResult/State/text()

Get State node : //GetCityForecastByZIPResult/State

Get list of forecast node ://GetCityForecastByZIPResult/ForecastResult/Forecast

Count No. of forecast node in message : count(//GetCityForecastByZIPResult/ForecastResult/Forecast)

Get list of nodes where DayHighTime is 95 : //Temperatures[DaytimeHigh=95]

Get name attribute value of State node : //State/@name

8.39. Perform

Perform test command allows users to perform various actions as follows.



8.39.1. Right Click

This action allows users to perform right click on a particular object.

8.39.2. Mouse Over

This action allows users to perform Mouse Over action on a particular object.

8.39.3. Scroll Up

This action allows users to perform scrolling up on a particular page.

8.39.4. Scroll Down

This action allows users to perform scrolling down on a particular page.

8.39.5. Close

This action allows users to close a particular page.

8.39.6. Set:variable

This action allows users to set a temporary variable to an object.

8.39.7. Accept Alert

This action allows users to accept the alerts/messages of the alert boxes.

8.39.8. Reject Alert

This action allows users to reject the alerts/messages of the alert boxes.

8.39.9. Set:globalvariable

This action allows users to set a permanent variable to an object. It is recommended to have a separate Test case for defining all the global variables.

8.39.10. Double Click

This action allows users to perform double click function on any button.

8.39.11. Drag and Drop

This action allows users to Drag and Drop facility on the web page.

8.40. Run Command

The Run Command test command allows users to execute the MS – DOS Commands.


Test Editor
Test Data
Outline
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Perform Select:value option_select Opel
9 Check Text Input button
10 Click reset
11 Run Command Test

[**Note:** *This Test command does not contain any Action*.]

8.41. Run Remote Command

This test command allows users to execute a Linux based commands to FTP Server.


Test Editor
Test Data
Outline
Enterprise Edition
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Select Value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
12 Run Remote Com...

8.42. Search

8.42.1. Object

The Search > Object test command allows users to Search the Object value in a particular direction on a webpage and store it into Object repository.


Test Editor
Test Data
Outline
Basic Element
Test Command Action Object Value Screenshot Description
1 Open Page http://testing-whiz.com...
2 Verify Title Testingwhiz - Basic Ele...
3 Input input_text Testing
4 Input input_password *******
5 Input input_textarea TestingWhiz™ is an Easy...
6 Click And Wait gender:on
7 Click And Wait hobbies2
8 Select Value option_select Opel
9 Check Text Input button
10 Click reset
11 Write Message To ... Basic element script
12 Search Object

8.43. Select



8.43.1. Value

This test command allows users to select a value of any object and variable. This can prevent unauthorized access of applications.

8.43.2. Index

This test command allows users to select an index of any object and variable. This can prevent unauthorized access of applications.

8.44. Send Mail

Send Mail test command allows users to send mails to desired email addresses easily during script execution. To execute this test command, users should have the required Mail configurations done.

[**Note:** *User needs to click on* *icon and enter* ***To*** *(Recipient's ID),* ***Subject*** *and* ***Message*** *as shown below.*]



[**Note:** *This Test command does not contain any Action*.]

8.45. Server



8.45.1. GET Request

This test command allows users to request in is used by app server to signal to the test script that the HTTP request has been received.

8.45.2. POST Request

This test command allows users to request out is used by app server to signal to the test script that the HTTP response has been dispatched.

8.45.3. Checkpoint

This test command allows users to Checkpoint is used to check whether the execution logic has passed via a line of code.

8.45.4. Callback

This test command allows users to Callback is used to call a java method in the web application from the test script.

8.46. Set

8.46.1. Value

This test command allows users to set a value of any object and variable. This can prevent unauthorized access of applications.



8.47. String

The String Test command allows users to perform various manipulations like Comparison, Finding the Length, etc. while working with the Strings.



8.47.1. Extract Substring

The Extract Substring action allows users to extract a range of characters as a Sub String from the given String.

[**Note:** *The extraction of substring would depend on the Begin and End Indexes specified by a user. If a user does not mention the End Index, then the length of the Sting would be considered as End Index.*]

8.47.2. To Lower

The To Lower action will convert the Uppercase letter to the corresponding Lowercase Letter.

8.47.3. To Upper

The To Upper action will convert the Lowercase letter to the corresponding Uppercase Letter.

8.47.4. Trim

The Trim action allows users to remove the leading and trailing blanks in the String.

8.47.5. Length

The Length action allows users to determine the length of the String.

8.47.6. Compare

The Compare action allows users to perform the Comparison between two stings i.e. verify whether two strings are equal or not. The Compare action will take the Case Sensitivity of the Strings into consideration.

8.47.7. Compare Ignore Case

The Compare Ignore Case action will work in the similar manner as Compare action, but with a little enhancement. This action will ignore the case sensitivity of the Strings at the time of comparison.

8.47.8. Concatenate

The Concatenate action will merge 2 Strings that is, it would append String2 at the end of String1.

8.47.9. IsBlankOrNull

The isBlankOrNull Test command enables a user to verify whether the value of a Variable is Null and not.

8.47.10. ToNumber

The ToNumber action will convert the numeric characters into the numbers with relevant data type.

8.47.11. Contains

The Contains action allows users to determine whether a string contains a given sub string.

8.47.12. Split

This action allows users to split the string into multiple parts by making use of a delimiter.

8.47.13. Remove

This action allows users to remove a part by specifying it in another string.

8.48. Trigger



8.48.1. Value

This test command allows users to check value is used by application code to tell test script to assign a value to an object during runtime

8.49. Verify

Verify test command allows users to verify any action. Verify test command will work same as Check test command. The only difference is that Verify test command will not stop the execution from the point where it fails.



8.49.1. Text

This action allows users whether the specified text is present on a page or not. The action will be performed for all the text on the page. The check will be performed by matching the case of the text value specified. Text with special symbols will not be considered. For e.g "hello" will be considered different from HELLO. Check test command will not stop the execution from the point where it fails.

8.49.2. Title

This action allows users to verify whether the title of a page has the specified value or not.

8.49.3. Checked

This action allows users to verify whether the checkbox is checked or selected.

8.49.4. Unchecked

This action allows users to verify whether the checkbox is unchecked or de-selected.

8.49.5. Visible

This action allows users to verify whether a specific object is visible on the page or not.

8.49.6. Invisible

This action allows users to verify whether a specific object is invisible/hidden on the page or not.

8.49.7. Enabled

This action allows users to verify whether the object (links, buttons etc.) is enabled on the page.

8.49.8. Disabled

This action allows users to verify whether the object (links, buttons etc.) is disabled on the page.

8.49.9. elected:index

This action allows users to verify whether the option of the specified index is selected in the dropdown list.

8.49.10. Selected:value

This action allows users to verify whether the option of the specified value is selected in the dropdown list.

8.49.11. Text:value

This action allows users to verify whether an object has the specified value or not. This test command can also be utilized by taking value from the text box. For e.g. when the values in the textbox are automatically populated from a database, a user can check/verify these values by taking id or object of the textbox.

8.49.12. Exists

This action allows users to verify whether the object exists on the page or not. Verify test command will not stop the execution from the point where it fails.

8.49.13. URL Reachable

This action allows users to verify if a supplied URL in value column is a valid URL or not.

8.49.14. Image

This action allows users to compare two images with URL to URL, File to File and URL to file comparison. This command will run as per the behavior of Verify functionality, which includes following scenarios:

A. The Verify command will fail if tolerance power given is less than actual difference in images.

B. The Verify command will pass if tolerance power given is greater than actual difference in images.

8.49.15. Test Ignore Case

This action allows users to verify whether the text is present on the page irrespective of the case of the text. The check will be performed by ignoring the case of the text value specified. Text with special symbols will not be ignored.

For e.g. "hello" will be considered same as HELLO. The check will be performed on all the contents that are present in the form of the text like labels, links etc. Verify test command will not stop the execution.

8.49.16. Cookie

This action allows users to check whether the page contains a specified cookie or not. The result of the cookie's presence or absence will be reflected in the log that is generated for the Report of the Test Case.

8.49.17. Single Occurance

This action allows users to verify whether the value occurs only one time on the page or not. The Single Occurrence action will occur only on page contents. It will not include page title, header etc. verify test command will not stop the execution.

8.50. Wait

Wait test command allows an element/object to wait till it is rendered on a page or for a specific time before the execution of the next action.

8.50.1. For Element

This action allows an object/element to wait for a specific time before the next action occurs.

8.50.2. For Time

This action allows users to wait for a specific time before the next action occurs.



8.51. While End

While End test command allows users to end a While loop of Test Steps for a defined condition.



[**Note:** *This Test command does not contain any Action*.]

8.52. While Start

While Start test command allows users to start a defined While Loop of Test Steps. To execute this loop, user can mention the condition for the loop.



[**Note:** *User needs to input data in* ***Value1, Condition, Value 2,*** *select* ***Operator*** *information and* ***Step By*** *position*.]

[**Note:** *A script with While Start test command should also contain While End test command to end the loop.*]

[**Note:** *This Test command does not contain any Action*.]

8.53. Write Message To Report

Write Message to Report test command allows users to write a particular message on the console and report window.



[**Note:** *This Test command does not contain any Action*.]